
Lebus® Load Binders







- Upgraded for use with Grades 70, 80 and 100 Chain.
- Utilizes standard Crosby A-323 Alloy Eye Grab Hooks.
- New design "one piece" forged handle.
- Continuous take-up feature provides finite adjustment to tie down load.
- One piece assembly, no bolts or nuts to loosen.
- Ratchet spring is rust proofed.
- All load bearing or holding parts forged.
- · Easy operating positive ratchet.
- Binders shown with Proof Loads have been individually proof tested to values shown, prior to shipment.



L-140 Standard Ratchet Type Load Binders


• Meets or exceeds requirements of US DOT FMCSA Part 393 Subpart I.

| | | Min-Max | Working | | | | | | Dimensions (in.) | | | | | | | |
|---------|-----------|---------------|---------------|---------------|----------------|------------------|------------------|------------|---------------------|------|------|-------|-------|-------|-------|-----|
| | | Chain Size | Load Limit | Proof Load | Weight Each | Handle Length | Barrel Length | Take Up | | | | | | | | |
| Model | Stock No. | (in.) | (lbs.)* | (lbs.) | (lbs.) | (in.) | (in.) | (in.) | Α | В | С | E | E1 | F | F1 | G |
| R-7 ** | 1048404 | 5/16-3/8 | 8800 | 17600 | 12.11 | 14 | 10 | 8.0 | 14.00 | 1.38 | 2.75 | 22.94 | 30.94 | 25.13 | 33.13 | .50 |
| R-A ** | 1048422 | 3/8-1/2 | 15000 | 30000 | 14.70 | 14 | 10 | 8.0 | 14.00 | 1.38 | 2.75 | 25.25 | 33.25 | 27.63 | 35.63 | .63 |
| R-C *** | 1048440 | 1/2-5/8 | 16000 | 32000 | 14.55 | 14 | 10 | 8.0 | 14.00 | 1.38 | 2.75 | 26.38 | 24.38 | 29.44 | 37.44 | .72 |

- * Ultimate Load is 3 times the Working Load Limit.
- ** Matches the Working Load Limit of Grade 100 chain for both sizes.
- *** Matches the Working Load Limit of Grade 100 chain for 1/2" size.



- For use with Grade 7 Transport Chain.
- Utilizes standard Crosby A-323 Alloy Eye Grab Hooks.
- New design "one piece" forged handle.
- Continuous take-up feature, infinite adjustment, gets the last half of chain.
- One piece assembly, no bolts or nuts to loosen.
- Ratchet spring is rust proofed.
- All load bearings or holding parts forged.
- Easy operating positive ratchet.
- Binders shown with Proof Loads have been individually proof tested to values shown, prior to shipment.



R-7QL QUIC-LINK Ratchet Load Binder

| | | Min-Max | Working | | | | | | Dimensions (in.) | | | | | | | |
|-------|-----------|----------|---------|--------|--------|--------|--------|-------|---------------------|------|------|-------|-------|-------|-------|-----|
| | | Chain | Load | Proof | Weight | Handle | Barrel | Take | | | | | | | | |
| | R-7QL | Size | Limit | Load | Each | Length | Length | Up | | | | | | | | i |
| Model | Stock No. | (in.) | (lbs.)* | (lbs.) | (lbs.) | (in.) | (in.) | (in.) | Α | В | C | E | E1 | F | F1 | G |
| R-7QL | 1048413 | 5/16-3/8 | 6600 | 13200 | 12.25 | 14 | 10 | 8.0 | 14.00 | 1.38 | 2.75 | 24.81 | 32.81 | 27.00 | 35.00 | .50 |

^{*} Ultimate Load is 3 times the Working Load Limit.