



Representative

Catalog Number: M975
Product ID: 7TAI029610R0030
UPC Number: 78621081630
EAN Number: 05414363155256
Status: Active

Non-Insulated Tubular Ring Terminal, Length 2.40 Inches, Width 1.12 Inches, Bolt Hole 1/2 Inch, Wire Range 4/0AN-250kcmil, Copper, Tin Plated, 50 Pack

- These non-insulated ring terminals are made of electrolytic copper for high conductivity.
- They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire).
- Application Tools: TBM6, TBM6S, WT3185

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39121432 Electrical terminals |
| IGCC | 4603 Electrical terminals |
| Brand Name | Sta-Kon |
| Type | Ring Terminal |
| Special Features | These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). |
| Standard | UL E9809 |
| Wire Size | 4/0AN-250MCM |
| Voltage Rating | 600V |
| Material | Copper |
| Color | Metallic |

European Specifications (ETIM)

| | |
|------------------------|---|
| ETIM | EC001051 Tube cable lug for copper conductors |
| Connecting angle | Straight |
| Flange shape | Ring shape |
| Slender flange model | N |
| Insulated | N |
| Material | Copper |
| Surface protection | Tinned |
| Number of fixing holes | 1 |

Packaging

| | |
|---------------------------|-----------------|
| Inner Quantity | 50 |
| Inner Dimensions (inches) | 6x4x4 |
| Outer Quantity | 250 |
| Outer Dimensions (inches) | 21.5x7.3x4.9 |
| Weight Uom | 10 lbs. per 100 |

Documents / Support Tools

| | |
|-----------------------------|----------------------|
| Technical Data Sheet CA | Available on Website |
| Technical Data Sheet Global | wsd-000219 |

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com