

Actual

Catalog Number: RA18-8

 Product ID:
 7TAI029810R0007

 UPC Number:
 78621080388

 EAN Number:
 05414363157588

Status: Active

Nylon Insulated Ring Terminal, Length .89 Inches, Width .26 Inches, Maximum Insulation .136, Bolt Hole #8, Wire Range #22-#16 AWG, Color Red, Tin Plated

- · Self-insulated with high dieletric-strength nylon sleeves.
- An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep.
- Application Tools: WT2000, WT112M, WT145C, ERG4001, WT145A
- Alternate Package Qty: RA863

North American Specifications (UNSPSC)		
UNSPSC	39121432 Electrical terminals	
IGCC	4603 Electrical terminals	
Brand Name	Sta-Kon	
Туре	Ring Terminal	
Special Features	Self-insulated with high dieletric-strength nylon	
	sleeves. An inner bronze insulation grip sleeve	
	lengthens the flexing radius of the conductor and	
	eliminates conductor creep.	
Standard	UL E9809	
Wire Size	22-16	
Voltage Rating	600V	
Material	Copper	
Color	Red	

European Specifications (ETIM)		
ETIM	EC001052 Solderless copper terminals for copper	
	conductors	
Flange shape	Ring shape	
Insulation	PA	
Colour insulation	Red	
Reel packaging	N	
AWG-range	22-16	
Surface protection	Tinned	

Packaging	
Inner Quantity	100
Inner Dimensions (inches)	2.09x1.1x3
Outer Quantity	500
Outer Dimensions (inches)	15.1x9.4x8.9
Weight Uom	0.25 lbs. per 100

<b>Documents / Support Tools</b>	
Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com