

Actual



Actual

Catalog Number: RB863

Product ID: 7TAI029850R0013 **UPC Number:** 78621081864 **EAN Number:** 05414363158790

Status: Active

Nylon Insulated Ring Terminal, Length .89 Inches, Width .31 Inches, Maximum Insulation .162, Bolt Hole #8, Wire Range #18-#14 AWG, Color Blue, Copper, Tin Plated, 1,000 Pack

- · Self-insulated with high dieletric-strength nylon sleeves.
- An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep.
- Application Tools: WT2000, WT112M, WT145C, ERG4001, WT145A
- Alternate Package Qty: RB14-8

North American Specifications (UNSPSC)		
UNSPSC	39121432 Electrical terminals	
IGCC	4603 Electrical terminals	
Brand Name	Sta-Kon	
Туре	Ring Terminal	
Special Features	Self-insulated with high dieletric-strength nylon	
	sleeves. An inner bronze insulation grip sleeve	
	lengthens the flexing radius of the conductor and	
	eliminates conductor creep.	
Standard	UL E9809	
Wire Size	18-14	
Voltage Rating	600V	
Material	Copper	
Color	Blue	

European Specifications (ETIM)		
ETIM	EC001052 Solderless copper terminals for copper	
	conductors	
Flange shape	Ring shape	
Insulation	PA	
Colour insulation	Blue	
Reel packaging	N	
AWG-range	18-14	
Material	Copper	
Surface protection	Tinned	

Packaging	
Inner Quantity	1000
Inner Dimensions (inches)	6.3x3.2x4.9
Outer Quantity	10000
Outer Dimensions (inches)	16x9.7x6.8
Weight Uom	0.25 lbs. per 100

Documents / Support Tools	
Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Thomas & Betts - USA

8155 T&B Blvd.

www.tnb.com

Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321



Email:techsupport@tnb.com