

Actual



Family

Catalog Number: RC333

 Product ID:
 7TAI029860R0052

 UPC Number:
 78621081974

 EAN Number:
 05414363159315

Status: Active

Nylon Insulated Ring Terminal, Length 1.00 Inches, Width .37 Inches, Maximum Insulation .210, Bolt Hole #6, Wire Range #12-#10 AWG, Color Yellow, Copper, Tin Plated, 500 Pack

- · Self-insulated with high dieletric-strength nylon sleeves.
- An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep.
- Application Tools: WT2000, WT112M, WT145C, ERG4001, WT145A
- Alternate Package Qty: RC10-6

North American Specifications (UNSPSC)	
UNSPSC	39121432 Electrical terminals
IGCC	4603 Electrical terminals
Brand Name	Sta-Kon
Туре	Ring Terminal
Special Features	Self-insulated with high dieletric-strength nylon
	sleeves. An inner bronze insulation grip sleeve
	lengthens the flexing radius of the conductor and
	eliminates conductor creep.
Standard	UL E9809
Wire Size	12-10
Voltage Rating	600V
Material	Copper
Color	Yellow

European Specifications (ETIM)		
ETIM	EC001052 Solderless copper terminals for copper	
	conductors	
Flange shape	Ring shape	
Insulation	PA	
Colour insulation	Yellow	
Reel packaging	N	
AWG-range	12-10	
Material	Copper	
Surface protection	Tinned	

Packaging	
Inner Quantity	500
Inner Dimensions (inches)	6.2x3.1x4.69
Outer Quantity	5000
Outer Dimensions (inches)	17x10x7.7
Weight Uom	1.88 lbs. per 1000

Documents / Support Tools	
Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	wsd-000269

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321



Email:techsupport@tnb.com