

Actual



Family

Catalog Number: RC753

 Product ID:
 7TAI029860R0066

 UPC Number:
 78621082017

 EAN Number:
 05414363159483

Status: Active

Nylon Insulated Ring Terminal, Length 1.37 Inches, Width .72 Inches, Maximum Insulation .210, Bolt Hole 1/2 Inch, Wire Range #12-#10 AWG, Color Yellow, Copper, Tin Plated, 500 Pack

- Self-insulated with high dieletric-strength nylon sleeves.
- An inner bronze insulation grip sleeve lengthens the flexing radius of the conductor and eliminates conductor creep.
- Application Tools: WT2000, WT112M, WT145C, ERG4001, WT145A
- Alternate Package Qty: RC10-12

North American Specifications (UNSPSC)		
UNSPSC	39121432 Electrical terminals	
IGCC	4603 Electrical terminals	
Brand Name	Sta-Kon	
Туре	Ring Terminal	
Special Features	Self-insulated with high dieletric-strength nylon	
	sleeves. An inner bronze insulation grip sleeve	
	lengthens the flexing radius of the conductor and	
	eliminates conductor creep.	
Standard	UL E9809	
Wire Size	12-10	
Voltage Rating	600V	
Material	Copper	
Color	Yellow	

European Specifications (ETIM)		
ETIM	EC001052 Solderless copper terminals for copper	
	conductors	
Flange shape	Ring shape	
Insulation	PA	
Colour insulation	Yellow	
Reel packaging	N	
AWG-range	12-10	
Material	Copper	
Surface protection	Tinned	

Packaging	
Inner Quantity	500
Inner Dimensions (inches)	6.1x5.1x4.19
Outer Quantity	5000
Outer Dimensions (inches)	6.2x4.9x3.1
Weight Uom	5.63 lbs. per 1000

Documents / Support Tools	
Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	wsd-000205

Hours: 7AM - 6PM CDT

Phone: (888) 862-3289

Monday-Friday

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd.



www.tnb.com Memphis, TN 38125

Fax: (901) 252-1321 Email:techsupport@tnb.com