Thomas&Betts





Wiring Duct T&B Catalog Number:

UPC Number: Status: **Description:**

TY1X2WPW6 78621096986 Active

Wiring Duct Wide Slot 1 Inch X 2 Inch Rigid PVC White Features





Wide fingers and slots increase rigidity and enable insertion of bundles. V-Shaped slot lead-in enables easier and faster wire installation. Rounded edges keep hands and wires free of abrasion. Non-slip cover does not slide easily and resists vibration. Flush cover attaches flush with sidewall for finished look. Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Versatile North American and DIN Standard mounding holes enables same duct for multiple applications. General Style Wide Slot Nominal Width (inches) 1 Nominal Height (inches) 2 Material Rigid PVC Color White Adhesive-Backed No Mounting Holes Yes Dimension Information 1.25 Length (feet) 6 Width (inches) 1.25 Height (inches) 2.10 A (inches) 1.25 Differes) 2.01 E (inches) 2.01 C (inches) 1.25 D (inches) 1.25 D (inches) 0.30 F (inches) 0.30 F (inches)
easier and faster wire installation. Rounded edges keep hands and wires free of abrasion.Non-slip cover does not slide easily and resists vibration. Flush cover attaches flush with sidewall for finished look.Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralVide SlotStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25B (inches)2.10A (inches)1.25B (inches)2.01C (inches)3.0F (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10Linches)0.10Linches)0.10Linches)0.10Linches)0.80Accessories & ComponentsCoverTY1CPW6
keep hands and wires free of abrasion.Non-slip cover does not slide easily and resists vibration. Flush cover attaches flush with sidewall for finished look.Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralStyleStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25Dimension Information1.25Length (feet)6Ginches)2.10A (inches)1.25B (inches)2.10C (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.28H (inches)0.40I (inches)0.80Accessories & ComponentsCoverTY1CPW6
Non-slip cover does not slide easily and resists vibration. Flush cover attaches flush with sidewall for finished look.Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralVide SlotStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25B (inches)2.10A (inches)1.25D (inches)2.10C (inches)1.25D (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
bration. Flush cover attaches flush with sidewall for finished look. Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications. General Style Wide Slot Nominal Width (inches) 1 Nominal Height (inches) 2 Material Rigid PVC Color White Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 1.25 Height (inches) 2.10 A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 1.25 D (inches) 1.25 D (inches) 1.25 D (inches) 1.36 G (inches) 1.36 G (inches) 0.30 F (inches) 0.28 H (inches) 0.28 H (inches) 0.30 F (inches) 0.28 H (inches) 0.30 F (inches) 0.28 H (inches) 0.28 H (inches) 0.28 H (inches) 0.30 F (inches) 0.28 H (inches) 0.30 F (inches) 0.28 H
finished look.Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25Height (inches)1.25Dinches)1.25I (inches)1.25Height (inches)0.30F (inches)1.25D (inches)1.25D (inches)1.25D (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.28H (inches)0.30F (inches)0.40CoverTY1CPW6
Dual score lines are designed to yield clean breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25B (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)1.25B (inches)0.30F (inches)0.28H (inches)0.30F (inches)0.30CoverTY1CPW6
breakoffs at the base of the slot and the duct. Ver- satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.01E (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.10I (inches)0.10I (inches)0.10CoverTY1CPW6
satile North American and DIN Standard mounding holes enables same duct for multiple applications.GeneralStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension Information1.25Length (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25B (inches)2.10C (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.800Accessories & ComponentsVitCPW6
Keneral Style Wide Slot Nominal Width (inches) 1 Nominal Height (inches) 2 Material Rigid PVC Color White Adhesive-Backed No Mounting Holes Yes Dimension Information 1 Length (feet) 6 Width (inches) 1.25 Height (inches) 2.10 A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 3.00 F (inches) 0.300 F (inches) 0.300 F (inches) 0.28 H (inches) 0.10 I (inches) 0.10 I (inches) 0.10 I (inches) 0.80 Accessories & Components TY1CPW6
GeneralStyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)3.0F (inches)3.0F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
StyleWide SlotNominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25B (inches)2.01E (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.10I (inches)0.10I (inches)0.10I (inches)0.80Accessories & ComponentsTY1CPW6
Nominal Width (inches)1Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)1.25B (inches)0.30F (inches)1.36G (inches)0.30F (inches)0.30F (inches)0.10I (inches)0.10I (inches)0.10I (inches)0.80Accessories & ComponentsTY1CPW6
Nominal Height (inches)2MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)1.25G (inches)1.25D (inches)1.25D (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)3.0F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
MaterialRigid PVCColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)3.0F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
ColorWhiteAdhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
Adhesive-BackedNoMounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)2.10C (inches)1.25D (inches)0.30F (inches)0.30F (inches)0.30F (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
Mounting HolesYesDimension InformationLength (feet)6Width (inches)1.25Height (inches)2.10A (inches)1.25B (inches)2.10C (inches)1.25D (inches)2.10C (inches)0.30F (inches)1.36G (inches)0.28H (inches)0.10I (inches)0.80Accessories & ComponentsCoverTY1CPW6
Dimension Information Length (feet) 6 Width (inches) 1.25 Height (inches) 2.10 A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 2.10 C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 0.30 F (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components TY1CPW6
Length (feet) 6 Width (inches) 1.25 Height (inches) 2.10 A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components TY1CPW6
Width (inches) 1.25 Height (inches) 2.10 A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
Height (inches) 2.10 A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80
A (inches) 1.25 B (inches) 2.10 C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
B (inches) 2.10 C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
C (inches) 1.25 D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
D (inches) 2.01 E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components TY1CPW6
E (inches) 0.30 F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
F (inches) 1.36 G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
G (inches) 0.28 H (inches) 0.10 I (inches) 0.80 Accessories & Components Cover TY1CPW6
H (inches) 0.10 I (inches) 0.80 Accessories & Components TY1CPW6
l (inches) 0.80 Accessories & Components Cover TY1CPW6
Accessories & Components Cover TY1CPW6
Cover TY1CPW6
T&B Order Multiple 120
T&B Inner Pack 6
Package in Units 120
T&B Sold in UOM Feet
T&B Weight Per UOM22.13 lbs. per 100
Application Support
Product Selector TD_selector_duct_white
T&B Sales Drawings wsd-000180
Technical Information Available on Website

Thomas&Betts

Specifications	Available on Website
Overview	Available on Website
Wire Fill Calculator	Available on Website
Notes	
Options	Catalog Number must be completed by adding suf- fix G for Gray, W for White, B for Black, I for Intrin- sic Blue. To order Adhesive-Backed duct, add suffix A. To order duct without mounting holes, add suffix NM to catalog number. Contact Customer Service for pricing and availability.
	Standard lengths are 6 feet.
Certifications	
RoHS Compliance	Yes
Webcat CE_recognized	Y
Certifications	



For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com