


Thomas@Betts







Wiring Duct T&B Catalog Number:

TY3X4RPG6 78621095738

UPC Number: Active Status:

Description:

ea	 	

Multiple rows of holes retain wire at different heights and positions with or without the cover. Features maximum number of wire holes. Rounded edges keep hands and wires free of abrasion. Non-slip cover does not slide easily and resists vibration. Cover attaches flush with sidewall for finished look. Base score line enables sidewall section to be removed. Integrated mounting holes - larger sizes include staggered holes for mounting flexibility. General Style Round Hole Nominal Width (inches) 3 Nominal Height (inches) 4 Material Rigid PVC Color Gray Hole Size (inches) 7/16" Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 4.46 C (inches) 4.39 E (inches) 4.39 E (inches) 4.00 G (inches) 4.39 E (inches) 4.00 G (inches) 4.00 G (inches) 4.00 G (inches) 6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Packaging TD_selector_duct_gray Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182 Technical Information Available on Website	Wiring Duct Round Hole 3 Inch X Features	4 Inch Rigid PVC Gray
moved. Integrated mounting holes - larger sizes include staggered holes for mounting flexibility. General		and positions with or without the cover. Features maximum number of wire holes. Rounded edges keep hands and wires free of abrasion. Non-slip cover does not slide easily and resists vibration. Cover attaches flush with sidewall for fin-
Style Round Hole Nominal Width (inches) 3 Nominal Height (inches) 4 Material Rigid PVC Color Gray Hole Size (inches) 7/16" Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support		moved. Integrated mounting holes - larger sizes in-
Nominal Width (inches) 3 Nominal Height (inches) 4 Material Rigid PVC Color Gray Hole Size (inches) 7/16" Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray	General	
Nominal Height (inches) 4 Material Rigid PVC Color Gray Hole Size (inches) 7/16" Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support TD_selector_duct_gray Product Selector TD_selector_duct_gray	·	
Material Rigid PVC Color Gray Hole Size (inches) 7/16" Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support TD_selector_duct_gray Product Selector TD_selector_duct_gray	· ,	
Color Gray Hole Size (inches) 7/16" Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		•
Hole Size (inches) 7/16" Rows of Holes 6 6 6 6 6 6 6 6 6		
Rows of Holes 6 Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		•
Adhesive-Backed No Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support TD_selector_duct_gray T&B Sales Drawings wsd-000182		
Mounting Holes Yes Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		
Dimension Information Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		
Length (feet) 6 Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		Yes
Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	Dimension Information	
Width (inches) 3.25 Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	Length (feet)	6
Height (inches) 4.46 A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		3.25
A (inches) 3.25 B (inches) 4.46 C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		
B (inches)		3.25
C (inches) 3.25 D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		4.46
D (inches) 4.39 E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		3.25
E (inches) 0.39 F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		4.39
F (inches) 4.00 G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		0.39
G (inches) 0.67 Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		4.00
Accessories & Components Cover TY3CPG6 Packaging T&B Order Multiple T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		0.67
Packaging T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	Accessories & Components	
T&B Order Multiple 60 T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	Cover	TY3CPG6
T&B Inner Pack 6 Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	Packaging	
Package in Units 60 T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	T&B Order Multiple	60
T&B Sold in UOM Feet T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	T&B Inner Pack	6
T&B Weight Per UOM 64 lbs. per 100 Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182	Package in Units	60
Application Support Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		Feet
Product Selector TD_selector_duct_gray T&B Sales Drawings wsd-000182		64 lbs. per 100
T&B Sales Drawings wsd-000182	Application Support	
	Product Selector	- ·
Technical Information Available on Website		wsd-000182
	Technical Information	Available on Website



Specifications	Available on Website
Overview	Available on Website
Wire Fill Calculator	Available on Website
Notes	
Options	Catalog Number must be completed by adding suffix G for Gray, W for White, B for Black, I for Intrinsic Blue. To order Adhesive-Backed duct, add suffix A. To order duct without mounting holes, add suffix NM to catalog number. Contact Customer Service for pricing and availability.
	Standard lengths are 6 feet.
Certifications	
RoHS Compliance	Yes
Webcat CE_recognized	Y
Certifications	





For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com