



Actual

Catalog Number: 14RB-8F
Product ID: 7TAI029450R0012
UPC Number: 78621080066
EAN Number: 05414363138051
Status: Active

Vinyl-Insulated Fork Terminal, Length .97 Inches, Width .31 Inches, Maximum Insulation .170, Bolt Hole #8, Wire Range #18-#14 AWG, Color Blue, Copper, Tin Plated

- These fork terminals have extra-long PVC insulation sleeve for protection and stress relief at wire's flex point.
- Brazed seam barrel is serrated for high pull-out value.
- Insulation is color-coded.
- Application Tools: WT145C, WT2000, WT112M, ERG4001
- Alternate Package Qty: RB657

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39121432 Electrical terminals |
| IGCC | 4603 Electrical terminals |
| Brand Name | Sta-Kon |
| Type | Fork Terminal |
| Special Features | These fork terminals have extra-long PVC insulation sleeve for protection and stress relief at wires flex point. Brazed seam barrel is serrated for high pull-out value. Insulation is color-coded. |
| Standard | UL E9809 |
| Wire Size | 18-14 |
| Voltage Rating | 600V |
| Material | Copper |
| Color | Blue |

European Specifications (ETIM)

| | |
|--------------------|--|
| ETIM | EC001052 Solderless copper terminals for copper conductors |
| Flange shape | Fork shape |
| Insulation | PVC |
| Colour insulation | Blue |
| Reel packaging | N |
| AWG-range | 18-14 |
| Material | Copper |
| Surface protection | Tinned |

Packaging

| | |
|---------------------------|-------------------|
| Inner Quantity | 100 |
| Inner Dimensions (inches) | 10.5x8.7x7.2 |
| Outer Quantity | 5000 |
| Outer Dimensions (inches) | 15x9.25x8.75 |
| Weight Uom | 2.5 lbs. per 1000 |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| Technical Data Sheet US | Available on Website |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Memphis, TN 38125
www.tnb.com

8155 T&B Blvd.
Memphis, TN 38125

Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com