



Actual

Catalog Number: 18RA-10
Product ID: 7TAI029450R0014
UPC Number: 78621080092
EAN Number: 05414363138440
Status: Active

Vinyl-Insulated Ring Terminal, Length .97 Inches, Width .31 Inches, Maximum Insulation .150, Bolt Hole #10, Wire Range #22-#16 AWG, Color Red, Copper, Tin Plated

- These terminals are self-insulated with a PVC insulation sleeve of extra length to give protection and relieve bending stress at wire's flex point.
- Brazed seam barrel is serrated to obtain high pull-out value.
- Application Tools: WT145C, WT2000, WT112M, ERG4001
- Alternate Package Qty: RA877

North American Specifications (UNSPSC)

| | |
|------------------|--|
| UNSPSC | 39121432 Electrical terminals |
| IGCC | 4603 Electrical terminals |
| Brand Name | Sta-Kon |
| Type | Ring Terminal |
| Special Features | These terminals are self-insulated with a PVC insulation sleeve of extra length to give protection and relieve bending stress at wires flex point. Brazed seam barrel is serrated to obtain high pull-out value. |
| Standard | UL E9809 |
| Wire Size | 22-16 |
| Voltage Rating | 600V |
| Material | Copper |
| Color | Red |

European Specifications (ETIM)

| | |
|--------------------|--|
| ETIM | EC001052 Solderless copper terminals for copper conductors |
| Flange shape | Ring shape |
| Insulation | PVC |
| Colour insulation | Red |
| Reel packaging | N |
| AWG-range | 22-16 |
| Material | Copper |
| Surface protection | Tinned |

Packaging

| | |
|---------------------------|-------------------|
| Inner Quantity | 100 |
| Outer Quantity | 500 |
| Outer Dimensions (inches) | 15x9.5x8.9 |
| Weight Uom | 0.25 lbs. per 100 |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| Technical Data Sheet US | Available on Website |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com