

Actual

Catalog Number: 18RA-14

 Product ID:
 7TAI029460R0027

 UPC Number:
 78621080096

 EAN Number:
 05414363138471

Status: Active

Vinyl-Insulated Ring Terminal, Length 1.13 Inches, Width .50 Inches, Maximum Insulation .150, Bolt Hole 1/4 Inch, Wire Range #22-#16 AWG, Color Red, Copper, Tin Plated

- These terminals are self-insulated with a PVC insulation sleeve of extra length to give protection and relieve bending stress at wire's flex point.
- Brazed seam barrel is serrated to obtain high pull-out value.
- Application Tools: WT145C, WT2000, WT112M, ERG4001
- Alternate Package Qty: RA717

North American Specifications (UNSPSC)		
UNSPSC	39121432 Electrical terminals	
IGCC	4603 Electrical terminals	
Brand Name	Sta-Kon	
Туре	Ring Terminal	
Special Features	These terminals are self-insulated with a PVC insulation sleeve of extra length to give protection and relieve bending stress at wires flex point. Brazed seam barrel is serrated to obtain high pull-out value.	
Standard	UL E9809	
Wire Size	22-16	
Voltage Rating	600V	
Material	Copper	
Color	Red	

European Specifications (ETIM)		
ETIM	EC001052 Solderless copper terminals for copper	
	conductors	
Flange shape	Ring shape	
Insulation	PVC	
Colour insulation	Red	
Reel packaging	N	
AWG-range	22-16	
Material	Copper	
Surface protection	Tinned	

Packaging	
Inner Quantity	100
Outer Quantity	500
Outer Dimensions (inches)	12.2x10.3x8.2
Weight Uom	2.5 lbs. per 1000

<b>Documents / Support Tools</b>	
Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com