



Representative

Catalog Number: B14-8
Product ID: 7TAI029580R0013
UPC Number: 78621080320
EAN Number: 05414363148463
Status: Active

Non-Insulated Ring Terminal, Length .75 Inches, Width .31 Inches, Bolt Hole #8, Wire Range #18-#14 AWG, Copper, Tin Plated

- These non-insulated ring terminals are made of electrolytic copper for high conductivity.
- They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire).
- Serrated barrel increases grip on wire.
- Application Tools: WT110M, WT111M, WT112M, WT2000, ERG4002
- Alternate Package Qty: B86

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39121432 Electrical terminals |
| IGCC | 4603 Electrical terminals |
| Brand Name | Sta-Kon |
| Type | Ring Terminal |
| Special Features | These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). Serrated barrel increases grip on wire. |
| Standard | UL E9809 |
| Wire Size | 18-14 |
| Voltage Rating | 600V |
| Material | Copper |
| Color | Metallic |

European Specifications (ETIM)

| | |
|--------------------|--|
| ETIM | EC001052 Solderless copper terminals for copper conductors |
| Flange shape | Ring shape |
| Insulation | None |
| Reel packaging | N |
| AWG-range | 18-14 |
| Material | Copper |
| Surface protection | Tinned |

Packaging

| | |
|---------------------------|-------------------|
| Inner Quantity | 100 |
| Inner Dimensions (inches) | 2.63x1.63x3.5 |
| Outer Quantity | 500 |
| Outer Dimensions (inches) | 15x9.4x8.7 |
| Weight Uom | 2.5 lbs. per 1000 |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| Technical Data Sheet US | Available on Website |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com