

Representative

Catalog Number: C10-6-SK

 Product ID:
 7TAI029580R0019

 UPC Number:
 78621080340

 EAN Number:
 05414363148944

Status: Active

Non-Insulated Ring Terminal, Length .82 Inches, Width .31 Inches, Bolt Hole #6, Wire Range #12-#10 AWG, Copper, Tin Plated

- These non-insulated ring terminals are made of electrolytic copper for high conductivity.
- They can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire).
- · Serrated barrel increases grip on wire.
- Application Tools: WT110M, WT111M, WT112M, WT2000, ERG4002
- Alternate Package Qty: C33

North American Specifications (UNSPSC)		
UNSPSC	39121432 Electrical terminals	
IGCC	4603 Electrical terminals	
Brand Name	Sta-Kon	
Туре	Ring Terminal	
Special Features	These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire). Serrated barrel increases grip on wire.	
Standard	UL E9809	
Wire Size	12-10	
Voltage Rating	600V	
Material	Copper	
Color	Metallic	

European Specifications (ETIM)		
ETIM	EC001052 Solderless copper terminals for copper	
	conductors	
Flange shape	Ring shape	
Insulation	None	
Reel packaging	N	
AWG-range	12-10	
Material	Copper	
Surface protection	Tinned	

Packaging	
Inner Quantity	50
Inner Dimensions (inches)	2.63x1.63x3.5
Outer Quantity	250
Outer Dimensions (inches)	15.1x9.4x8.9
Weight Uom	5 lbs. per 1000

Documents / Support Tools	
Technical Data Sheet US	Available on Website
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...



8155 T&B Blvd. Memphis, TN 38125 www.tnb.com MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com