



Long Barrel Copper Lug
T&B Catalog Number:

LCN350
 78378603255
 Active

UPC Number:
Status:
Description:

Copper Two-Hole Lug - Straight Long Barrel - max 35KV, 350 kcmil Wire, 1/2 Bolt Size, Tin Plated, Red

Features

- Made of high-conductivity seamless copper tubing. Tin plated for corrosion resistance.
- Specifically chamfered barrel for ease of installation.
- Color-coded for matching die identification.
- UL Listed for AWG conductor when installed with Blackburn, Burndy, T&B or Andersons Tools.
- Complies with Subpart 111.60-17 of Federal Register's Coast Guard Electrical Engineering Rules and Regulations.

General

| | |
|-------------------|------------|
| Material | Copper |
| Finish | Tin Plated |
| Wire Size | 350 kcmil |
| Number of Studs | 2 |
| Stud Size | 1/2 |
| Bolt Hole Spacing | 1 3/4 |
| Tongue Angle | Straight |
| Barrel Length | Long |
| Barrel Shape | Standard |
| Die Color | Red |

Dimension Information

| | |
|------------|---------|
| A (inches) | 1 27/32 |
| B (inches) | 3 |
| C (inches) | 1/2 |
| L (inches) | 5 11/32 |
| T (inches) | 5/32 |
| W (inches) | 1 11/32 |

Specifications

| | |
|----------------|------|
| Voltage Rating | 35KV |
|----------------|------|

Tooling

| | |
|---------------------------|----------------------|
| Connector & Tooling Chart | Available on Website |
|---------------------------|----------------------|

Packaging

| | |
|--------------------|-------------------|
| T&B Inner Pack | 10 |
| Package in Units | 100 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 41.6 lbs. per 100 |

Notes

For use with copper conductor: AWG, stranded, flexible cable, welding cable and portable cord. Specially designed for industrial and building applications.

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

Y

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com