

Weatherproof Metallic Boxes

Universal Boxes and Covers

Applications:


- Dry-tite[™] boxes and covers protect wiring devices. switches, electronic components and terminal blocks in dry, damp and wet locations
- Accessible wiring chamber provides a convenient location to maintain or change a system, pull conductors and make splices
- Junction box for branch conduits

Features/Benefits:

- Alloy A380 aluminum, certified zinc alloy and stainless steel springs provide increased corrosion resistance
- Die-cast construction and industrial design combine to produce a rugged protective enclosure for devices on many applications
- Clean cover edges provide good gasket sealing
- Precision-cast and machined surfaces permit safer wire pulling
- Clear UL and cubic content markings speed approval by inspectors
- Convenient mounting lugs for a variety of mounting methods
- Securely fastened mounting plates reduce costly call backs

Standard Materials:

- Boxes: Die-cast aluminum alloy A380
- Cover Plates: Stamped aluminum alloy or certified die-cast zinc alloy ZAMAK 3
- Cover Lids: Certified die-cast zinc alloy ZAMAK 3



Standard Finish:

Powder-coated finish

Compliances:

- UL® Listed (UL File No. E-2969)
- Boxes: CSA Certified with factory installed ground screw**
- Covers: CSA Certified
- Covers suitable for use in wet locations with covers closed
- CCB and CCT series covers suitable for use in wet locations
- Federal Spec. W-C-586
- NEMA 3R Rated

Sample Specifications:

 Universal device boxes and covers shall be of aluminum alloy A380 and certified zinc alloy. All conduit stops shall be free of rough edges. Covers shall have stainless steel springs. Covers shall be finished with powder-coated paint. Universal device boxes and covers shall be Red • Dot® Catalog No.



Accessible wiring chamber provides a convenient location to pull conductors and make splices in dry, damp or wet locations.

- Maximum cubic capacity
- Securely fastened mounting plates
- Corrosion-resistant materials
- Powder-coated finish
- Ground screw included
- Precision-machined threads
- Clear UL and cubic volume marking



IH3-1-LM



United States

Tel: 901.252.8000 800.816.7809 Fax: 901.252.1354

Technical Services

www.tnb.com Tel: 888.862.3289




Weatherproof Metallic Boxes

Single-Gang

	CAT. NO.	HUB SIZE (IN.)	COLOR	OUTLETS	3
Three Outlets					
	IH3-1	1/2	Silver	Тор	1
	IH3-2	3/4	Silver	Bottom	1
_	IH3-1-LM●	1/2	Silver	Back	1
A Second	H3-2-LM•	3/4	Silver	TOTAL	3
	D-PAK®				
9	DIH3-1-LM●	1/2	Silver		
	DIH3-1-LM-BR•	1/2	Bronze		
	DIH3-1-LM-WH•	1/2	White		
	DIH3-2-LM•	3/4	Silver		
	DIH3-3-LM	1	Silver		

Four Outlets



Five Outlets



IIH5-1	1/2	Silver	Top	2
IH5-2	3/4	Silver	Bottom	2
IH5-1-LM●	1/2	Silver	Back	1
IH5-2-LM•	3/4	Silver	TOTAL	5
D-PAK®				
DIH5-1-LM●	1/2	Silver		
DIH5-2-LM•	3/4	Silver		

Five Outlets (2-Side)



			TOTAL	5
			Back	1
			Side	1
			Side	1
IH5S2-2•	3/4	Silver	Bottom	1
IH5S2-1•	1/2	Silver	Тор	1

Six Outlets (3-Side)



			TOTAL	6
			Back	1
			Side	1
			Side	2
IH6S2-2•	3/4	Silver	Bottom	1
IH6S2-1•	1/2	Silver	Top	1
<i>6)</i>				

Note: Raintight when used with appropriate Red \bullet Dot® covers. Boxes supplied with 2 closure plugs and ground screw.

• With mounting lugs

Two-Gang

	CAT. NO.	HUB SIZE (IN.)	OUTLETS	S
Three Outlets				
	2IH3-1•	1/2	Top	1
1121	2IH3-2•	3/4	Bottom	1
			Back	1_
- B. B. B.			TOTAL	3
	D-PAK®			
	D2IH3-1	1/2		

Four Outlets



		TOTAL	4
		Back	1
2IH4-2•	3/4	Bottom	1
2IH4-1•	1/2	Тор	2

Five Outlets



7			TOTAL	5
			Back	1
21H5-1•	2IH5-2•	3/4	Bottom	2
	2IH5-1•	1/2	Тор	2

Five Outlets (2-Side)



			TOTAL	5
			Back	1
			Side	1
9			Side	1
Вī	2IH5S2-2•	3/4	Bottom	1
	2IH5S2-1•	1/2	Тор	1

Seven Outlets



2H7-2•			TOTAL	7
The state of the s	1		Back	1
ZIH7-1♥ //2 10p	2IH7-2•	3/4	Bottom	3
01U7 1. Top	2IH7-1•	1/2	Тор	3

Seven Outlets (2-Side)

A	00	1
1	3	1
		,

		ΤΩΤΔΙ	7
		Back	1
		Side	1
		Side	1
2IH7S2-2•	3/4	Bottom	2
2IH7S2-1•	1/2	Тор	2

Note: Raintight when used with appropriate Red•Dot® covers. Boxes supplied with 2 closure plugs and ground screw.

· With mounting lugs

