Steel City®

Square Boxes and Accessories

Box Support Covers

Steel City® Box Support Covers combine a box-to-stud mounting bracket with a device cover in one, easy-to-use product. Designed for use with 4" square boxes, Steel City® Box Support Covers can be used with both steel and wood studs.

- Combines cover and bracket in one component
- · Available in one- and two-device versions
- ½", 5%" and 34" raised covers
- Speeds installation time

DEPTH

(IN.)

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

1/2

CAT. NO.

RS 1

RS 2*

RS 3*

RS 4

RS₅

RS 8*

RS 9

RS 10

RS 11

RS 12*

RS 13

RS 14

RS 15

RS-16-CC

RS-17-CC

RS-18-CC

RS-19-CC*

- Needs no far side support
- Can be used with both steel and wood stud
- · Can be used without a box as a low voltage device support
- UL and CSA Listed (UL File #E2969, CSA File #LR5043)







52CMD17



CAT. NO.	RAISED (IN.)	# OF DEVICES	CU. IN. Capacity	STD. CTN.
52CM13	1/2	1	3.0	25
52CM14-5/8	5/8	1	4.0	25
52CM14	3/4	1	5.0	25
52CMD17	1/2	2	6.3	25
52CMD18-5/8	5/8	2	7.3	25
52CMD18	3/4	2	9.0	25

4" Square Surface Covers

CU. IN.

CAPACITY

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0

5.0



RS 4

DESCRIPTION

For one toggle switch and

one single flush receptacle

For one toggle switch and

113/32 For one single and one duplex

For two toggle switches

For one toggle switch

or range receptacle

receptacle

flush receptacle

receptacle

one duplex flush receptacle

For one 4-wire twist-lock single

For two duplex, flush receptacles

For two single, flush receptacles

For one single, flush receptacle

For one duplex, flush receptacle

For #3330-30A 250 V twist-lock

For one ground fault receptacle

For two ground fault receptacles

For one ground fault receptacle

For one ground fault receptacle

and one duplex receptacle

and one toggle switch

For one 30 or 50 amp. dryer

DIA.

HOLE



			1 0 0
RS 1		RS	S 2

STD.

CTN.

50

50

50

50

50

50

50

50

50

50

50

50

50

25

25

25

25



RS 3









᠖

RS 11



D


RS 12



RS 10



RS 13





RS 15



RS-16-CC




RS-17-CC





RS-19-CC



25/32

215/32

13/4



United States Tel: 901.252.8000

800.816.7809 Fax: 901.252.1354

Technical Services Tel: 888.862.3289

