

## **Steel City**<sup>®</sup>

## **Square Boxes and Accessories**



CAT. NO.	CU. IN. Capacity	DESCRIPTION	STD. CTN.
601-CD	8.8	$1\frac{1}{4}$ " raised — $4\frac{11}{6}$ " square	25
		Open plaster ring with ears. Ears tapped 8/32-223/32"	
		on centers. Special screw lock feature in slots*	
604-F	_	Flat — 4 <sup>11</sup> /16" square	25
		For two switches or receptacles*	
604-B	2.8	1/4" raised — 411/16" square	25
		For two switches or receptacles*	
*Fits anv Ste	el Citv® 411/16" s	quare outlet box or extension ring.	

## 4<sup>11</sup>/<sub>16</sub>" Square Surface Covers



RSL 16

RSL 17



RSL 19



CAT. NO	).	CU. IN. Capacity	DESCRIPTION	STD. CTN.
608-C		12.5	1" raised — 4 <sup>11</sup> / <sub>16</sub> " square	10
			For two switches or receptacles*	

\*Fits any Steel City<sup>®</sup> 411/16" square outlet box or extension ring.

## 4<sup>11</sup>/<sub>16</sub><sup>11</sup> Square Box Partitions

Thomas®Betts



CAT. NO.	STD. DESCRIPTION CTN.	
For 11/2" Dee	p Box with Square-Cut Tile Wall — Two-I	Device Covers
72 PS 1	For 1/2", 3/4" and 1" raised covers	25
72 PS 2	For $1\frac{1}{4}$ ", $1\frac{1}{2}$ " and 2" raised covers	25
For 21/8" Dee	ep Box with Square-Cut Tile Wall — Two-	Device Covers
72 PD 1	For 1/2", 3/4" and 1" raised covers	25
72 PD 2	For 11⁄4", 11⁄2" and 2" raised covers	25

CAT. NO.	DEPTH (IN.)	CU. IN. Capacity	DIA. Hole (IN.)	DESCRIPTION	STD. CTN.
RSL 2	1/2	7.5	-	For one toggle switch and one duplex flush receptacle	10
RSL 4	1/2	7.5	111/32	For one 4-wire twist-lock single receptacle	10
RSL 5	1/2	7.5	—	For two toggle switches	10
RSL 8	1/2	7.5	—	For two duplex, flush receptacles	10
RSL 9	1/2	7.5	15/32	For one toggle switch	10
RSL 11	1/2	7.5	1 <sup>55</sup> ⁄64	For one single, flush receptacle	10
RSL 12	1/2	7.5	—	For one duplex, flush receptacle	10
RSL 13	1/2	7.5	25/32	For one 30A to 50A dryer or range receptacle	10
RSL 14	1/2	7.5	215/32	-	10
RSL 15	1/2	7.5	1¾	For #3330–30A 250 V twist-lock receptacle	10
RSL 16	1/2	7.5	—	For one ground fault receptacle	10
RSL 17	1/2	7.5	_	For two ground fault receptacles	10
RSL 18	1/2	7.5	—	For one ground fault receptacle and one toggle switch	10
RSL 19	1/2	7.5	—	For one ground fault receptacle and one duplex receptacle	10

**Technical Services** Tel: 901.252.8000 Tel: 888.862.3289

**United States** 

800.816.7809 Fax: 901.252.1354

