

## Bushings, Nipples, Locknuts and Plugs

Perfect for grounding old work or new!

### Bonding & Grounding Wedges

- Provides grounding without a jumper except in concentric knockouts
- When jumper is required, it fits under set screw in grounding wedge
- Update existing installations to meet code requirements for bonding (NEC® Article 250, Part V) without disconnecting wiring
- For use on new wiring, just loosen bushing, position wedge and tighten bushing and bonding screw

#### Application

- To effectively bond terminating fitting or conduit to a box or enclosure

#### Features

- Sizes 3/4" thru 6" equipped with an additional bonding screw to install bonding jumper where required
- Can be added to an existing installation without disconnecting conductors

#### Standard Material/Finish


1/2" size Steel/Electro Zinc Plated  
3/4" thru 6" size Bronze/Tin Plated

#### Listings/Compliances


UL File #E3060  
CSA File #638  
UL 467  
CSA C22.2 No. 41  
NFPA-70  
Federal Specification A-A-50552

#### Range

1/2" thru 6" conduit



Series 3650



Series 3651

#### Grounding Wedges



CAT. NO.	SIZE
3650	1/2"
3651	3/4"
3652	1"
3653	1 1/4"
3654	1 1/2"
3655	2"
3656	2 1/2"
3657	3"
3658	3 1/2"
3659	4"
3661	5"
3662	6"

UL File No. E-3060

Sealing material resists oil, coolants and hydraulic fluids as well as water!

### Liquidtight Sealing Gasket

The 5262 Series Sealing Gasket includes a stainless steel retaining ring to prevent elongation of the Santoprene® gasket, ensuring a superior seal.

#### Application

- When used with an externally threaded connector, provides a tight seal against oil, fumes or moisture at the knockout opening

#### Features


- Design locks resilient sealing material in steel
- Steel retainer protects seal from extruding out under torque and limits compression to an optimum predetermined value; provides high quality seal
- Resilient material flows and seals rough surfaces
- NEMA 3R, 4, 6 and 13

#### Standard Material


Retainer: 316 Stainless Steel  
Sealing Material: Santoprene® Thermoplastic Rubber

#### Range

1/4" thru 4" Hub Size



5262 Series Sealing Gasket



Resilient Sealing Material Locked in Steel Retainer



CAT. NO.	CONDUIT SIZE	DIMENSIONS (IN.)		STD. PKG. QTY.
		A	B	
5262	1/2"	1.16	.18	50
5263	3/4"	1.49	.19	25
5264	1"	1.75	.19	25
5265	1 1/4"	2.15	.22	5
5266	1 1/2"	2.42	.23	5
5267	2"	2.92	.23	5
5268	2 1/2"	3.44	.23	5
5269	3"	4.08	.23	5
5270	4"	5.29	.31	5

UL File No. E 13938 CSA File No. 2884

Santoprene is a registered trademark of Advanced Elastomer Systems.