


Conduit Bodies and Fittings (for use with Schedule 40 and 80 Conduit)

Adapters



Adapts non-metallic conduit to all electrical enclosures by inserting adapter through knockout and cementing into Carlon couplings.



Box Adapters for Enclosures

CAT. NO.	SIZE (IN.)	STD. CTN.	MIN D (IN.)	OD (IN.) TYPICAL	MAX X (IN.)	CM (IN.) TYPICAL	L (IN.) TYPICAL
E996D	½	100	.662	.840	1 ¹ / ₆₄	2 ³ / ₃₂	2 ⁷ / ₃₂
E996E	¾	100	.824	1.050	1 ² / ₆₄	2 ³ / ₃₂	2 ⁷ / ₃₂
E996F	1	100	1.049	1.315	1 ¹ / ₆	6 ¹ / ₆₄	1 ¹ / ₃₂
E996G	1¼	50	1.380	1.660	1 ³ / ₃₂	1 ¹ / ₁₆	1¼
E996H	1½	50	1.610	1.900	2 ¹ / ₆₄	1 ¹ / ₁₆	1 ³ / ₈
E996J	2	25	2.067	2.375	2 ²⁹ / ₃₂	1¼	1 ¹ / ₁₆
E996K	2½	15	2.469	2.875	3 ⁷ / ₁₆	1 ¹ / ₆	1 ¹⁵ / ₁₆
E996L	3	20	3.068	3.500	4 ¹ / ₆	2	2 ¹ / ₁₆
E996N	4	10	4.026	4.500	5 ¹ / ₆	2½	2¼

Threaded Adapters

CAT. NO.	SIZE (IN.)	STD. CTN.
E9842D ¹	½	25
E9842E ²	¾	25



¹ Fits ¾" sockets
² Fits 1" sockets

Plugs

SP LR31146
UL LISTED E23018
Except where noted by ▶

Reducer Plugs

CAT. NO.	SIZE (IN.)	STD. CTN.	STD. WT. (LBS.)
▶ E971C	¾ x ½	100	2
▶ E971D	1 x ¾	100	3



Plugs (Polyethylene)

CAT. NO.	SIZE (IN.)	STD. CTN.	STD. WT. (LBS.)
▶ P258H	1½	50	2
▶ P258K	2½	25	1.5



Plugs with Pull Tabs (Polyethylene)


CAT. NO.	SIZE (IN.)	STD. CTN.	STD. WT. (LBS.)
▶ P258JT	2	60	3
▶ P258LT	3	30	3
▶ P258NT	4	48	8
▶ P258PT	5	30	6
▶ P258RT	6	30	9



Reducers



For connecting different sizes of conduit.
Bell x Spigot.



Reducer Bushings

CAT. NO.	SIZE (IN.)	STD. CTN.	L (IN.) TYPICAL	A (IN.) TYPICAL	C (IN.) TYPICAL
E950ED	¾ x ½	100	1 ¹ / ₃₂	1 ¹ / ₆₄	1 ¹ / ₃₂
E950FD-CAR	1 x ½	25	1 ¹¹ / ₃₂	¾	5 ¹ / ₆₄
E950FE	1 x ¾	100	1 ¹¹ / ₃₂	¾	1 ¹ / ₆₄
E950GE-CAR	1¼ x ¾	10	1 ¹⁵ / ₃₂	¾	1 ¹ / ₆₄
E950GF	1¼ x 1	50	1 ¹⁵ / ₃₂	¾	1 ¹ / ₆₄
E950HF-CAR	1½ x 1	10	1 ¹⁹ / ₃₂	¾	1 ¹ / ₆₄
E950HG-CAR	1½ x 1¼	10	1 ¹⁹ / ₃₂	¾	1 ¹ / ₆₄
E950JG-CAR	2 x 1¼	10	1¾	7 ¹ / ₃₂	1 ¹⁷ / ₆₄
E950JH-CAR	2 x 1½	10	1¾	7 ¹ / ₃₂	1 ²⁵ / ₆₄
E950KJ-CAR	2½ x 2	10	2 ⁵ / ₃₂	¾	1 ²⁷ / ₆₄
E950LJ-CAR	3 x 2	10	2 ¹ / ₆	¾	1 ¹ / ₆
▶ E950LK	3 x 2½	25	1 ¹⁵ / ₁₆	¼	1 ¹¹ / ₁₆
E950NL	4 x 3	25	2¼	¾	1 ¹⁵ / ₁₆

Fabricated Reducers

CAT. NO.	SIZE (IN.)	STD. CTN.	STD. WT. (LBS.)
Male x Male			
▶ E952JH	1½ x 2	48	20
▶ E952KJ	2½ x 2	48	26
▶ E952LJ	3 x 2	36	21
▶ E952LK	3 x 2½	36	32
▶ E952NL	4 x 3	15	21
▶ E952NM	4 x 3½	15	25
▶ E952PN	5 x 4	12	27
▶ E952RP	6 x 5	10	31
Male x Female			
▶ E952NJF	4 x 2	15	16
▶ E952RNF	6 x 4	10	28