



Actual

**Catalog Number:** L-14-120-0-C  
**Product ID:** 7TAG054410R0003  
**UPC Number:** 72849491160  
**EAN Number:** 05414363078005  
**Status:** Active

Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 362.81mm (14.284 Inches), Width of 7.62mm (0.30 Inches), Thickness of 1.91mm (0.075 Inches), Tensile Strength Rating of 534 Newtons (120 Pounds)

- Application Tools: ERG120

### North American Specifications (UNSPSC)

|                  |  |
|------------------|--|
| UNSPSC           | 39121703 Cable ties                    |
| IGCC             | 5034 Cable ties                        |
| Brand Name       | Catamount                              |
| Type             | Heavy-Duty                             |
| Standard         | UL E49405                              |
| Width            | 0.30 Inches/7.62mm                     |
| Length           | 14.284 Inches/362.81mm                 |
| Thickness        | 0.075 Inches/1.91mm                    |
| Bundle Diameter  | 0.187 Inches/4.76mm-4.0 Inches/101.6mm |
| Material         | Nylon/Polyamide 6.6 Weather Resistant  |
| Color            | Black                                  |
| Lock Mechanism   | Double Locking Head                    |
| Tensile Strength | 120 Pounds/534 Newtons                 |

### European Specifications (ETIM)

|                          |                    |
|--------------------------|--------------------|
| ETIM                     | EC000046 Cable tie |
| Band width               | 7.62mm             |
| Length belt/tape/tie     | 362.81mm           |
| Tie thickness            | 1.91mm             |
| Min. holding force       | 534N               |
| Model                    | Internal toothing  |
| Band closure             | Double lock head   |
| Material                 | Plastic            |
| Material quality         | Polyamide PA       |
| Halogen free             | Y                  |
| Colour                   | Black              |
| Transparent              | N                  |
| Reflective (fluorescent) | N                  |
| Text strip               | None               |
| Solvable fastener        | N                  |

### Packaging

|                           |                   |
|---------------------------|-------------------|
| Inner Quantity            | 100               |
| Inner Dimensions (inches) | 20x6x3            |
| Outer Quantity            | 3000              |
| Outer Dimensions (inches) | 18.25x13x13.5     |
| Weight Uom                | 1.38 lbs. per 100 |

### Documents / Support Tools

|                             |                      |
|-----------------------------|----------------------|
| Technical Data Sheet CA     | Available on Website |
| Technical Data Sheet Global | wsd-000223           |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)