



Actual

Catalog Number: L-5-30-9-C
Product ID: 7TAG054100R0047
UPC Number: 72849491560
EAN Number: 05414363078104
Status: Active

Intermediate Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, Length of 140mm (5.51 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1.2mm (0.05 Inches), Tensile Strength Rating of 178 Newtons (40 Pounds)

- Application Tools: ERG50, QC-100, L-200, L-400-C

North American Specifications (UNSPSC)

| | |
|------------------|------------------------|
| UNSPSC | 39121703 Cable ties |
| IGCC | 5034 Cable ties |
| Brand Name | Catamount |
| Type | Intermediate |
| Standard | UL E49405 |
| Width | 0.14 Inches/3.6mm |
| Length | 5.51 Inches/140mm |
| Thickness | 0.05 Inches/1.2mm |
| Bundle Diameter | to 1.25 Inches/31.75mm |
| Material | Nylon/Polyamide 6.6 |
| Color | Natural |
| Lock Mechanism | Double Locking Head |
| Tensile Strength | 40 Pounds/178 Newtons |

European Specifications (ETIM)

| | |
|--------------------------|--------------------|
| ETIM | EC000046 Cable tie |
| Band width | 3.6mm |
| Length belt/tape/tie | 140mm |
| Tie thickness | 1.2mm |
| Min. holding force | 178N |
| Model | Internal toothing |
| Band closure | Double lock head |
| Material | Plastic |
| Material quality | Polyamide PA |
| Colour | Natural colour |
| Transparent | N |
| Reflective (fluorescent) | N |
| Text strip | None |
| Solvable fastener | N |

Packaging

| | |
|---------------------------|-----------------|
| Inner Quantity | 100 |
| Inner Dimensions (inches) | 9x5x.75 |
| Outer Quantity | 20000 |
| Outer Dimensions (inches) | 18.4x13.1x13.3 |
| Weight Uom | 5 lbs. per 1000 |

Documents / Support Tools

| | |
|-----------------------------|----------------------|
| Technical Data Sheet CA | Available on Website |
| Technical Data Sheet Global | wsd-000290 |

For further technical assistance, please contact us...

Memphis, TN 38125
www.tnb.com

8155 T&B Blvd.
Memphis, TN 38125

Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com