



Actual

Catalog Number: L-7-50-9-M
Product ID: 7TAG054330R0008
UPC Number: 72849491730
EAN Number: 05414363128564
Status: Active

Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 188.85mm (7.435 Inches), Width of 4.73mm (0.186 Inches), Thickness of 1.35mm (0.053 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Bulk Pack

- Application Tools: ERG50, QC-100, L-200, L-400-C

North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Brand Name	Catamount
Type	Standard
Standard	UL E49405
Width	0.186 Inches/4.73mm
Length	7.435 Inches/188.85mm
Thickness	0.053 Inches/1.35mm
Bundle Diameter	0.0625 Inches/1.59mm-1.75 Inches/44.45mm
Material	Nylon/Polyamide 6.6
Color	Natural
Lock Mechanism	Double Locking Head
Tensile Strength	50 Pounds/220 Newtons

European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	4.73mm
Length belt/tape/tie	188.85mm
Tie thickness	1.35mm
Min. holding force	222N
Model	Internal toothing
Band closure	Double lock head
Material	Plastic
Material quality	Polyamide PA
Colour	Natural colour
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N

Packaging

Inner Quantity	1000
Inner Dimensions (inches)	17x12x3
Outer Quantity	10000
Outer Dimensions (inches)	18.25x13x13.5
Weight Uom	2.5 lbs. per 1000

Documents / Support Tools

Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	wsd-000222

For further technical assistance, please contact us...