



Actual

Catalog Number: L-8-40-0-C
Product ID: 7TAG054200R0001
UPC Number: 72849491820
EAN Number: 05414363128601
Status: Active

Intermediate Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 215mm (8.46 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1.2mm (0.05 Inches), Tensile Strength Rating of 178 Newtons (40 Pounds)

- Application Tools: ERG50, QC-100, L-200, L-400-C

North American Specifications (UNSPSC)

UNSPSC	39121703 Cable ties
IGCC	5034 Cable ties
Brand Name	Catamount
Type	Intermediate
Standard	UL E49405
Width	0.14 Inch/3.6mm
Length	8.46 Inches/215mm
Thickness	0.05 Inch/1.2mm
Bundle Diameter	0.0625 Inches/1.59mm-2.0 Inches/50.8mm
Material	Nylon/Polyamide 6.6 Weather Resistant
Color	Black
Lock Mechanism	Plastic Pawl
Tensile Strength	40 Pounds/178 Newtons

European Specifications (ETIM)

ETIM	EC000046 Cable tie
Band width	3.6mm
Length belt/tape/tie	215mm
Tie thickness	1.25mm
Max. bundle diameter	56mm
Min. holding force	40N
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamide PA
Surface protection	Other
Halogen free	Y
Colour	Black
Transparent	N
Reflective (fluorescent)	N
Text strip	None

Packaging

Inner Quantity	100
Inner Dimensions (inches)	12x4.85x.85
Outer Quantity	10000
Outer Dimensions (inches)	17.5x13.2x10.5
Weight Uom	5 lbs. per 1000

Documents / Support Tools

Technical Data Sheet CA	Available on Website
Technical Data Sheet Global	wsd-000221

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com