

Catalog Number: Product ID: UPC Number: Status:

RBBS22X 7TAI029900R0003 78621022391 A



Heat Shrinkable Butt Splice, Length 1.50 Inches, Width .26 Inches, Maximum Insulation Diameter .200, Wire Range #16-#14 AWG, Color Blue, Copper, Tin Plated, 500 Pack

- Self-insulated with heat-shrinkable polyolefin and internally coated sealant. Upon completed installation, a fully sealed connection is achieved to protect the joint against the degrading effects of galvanic action, corrosion, and environmental exposure.
- Application Tools: WT1255
- Alternate Package Qty: 2RBS14X

North American Specifications (UNSPSC)

North American opecifications (onor ob)		
UNSPSC	39121449 Wire or cable compression splice	
IGCC	4669 Wire or cable compression splice	
Brand Name	Sta-Kon	
Туре	Splice Connector	
Special Features	Self-insulated with heat-shrinkable polyolefin and internally coated sealant. Upon completed installa- tion, a fully sealed connection is achieved to protect the joint against the degrading effects of galvanic action, corrosion, and environmental exposure.	
Standard	UL E9809	
Material	Copper	
Finish	Electro -Tin Plated	
Color	Blue	
Voltage Rating	600 V	
Temperature Rating	150 Degrees C	

European Specifications (ETIM)

	· /
ETIM	EC001059 Crimp splices for copper conductor
AWG-range	16-14
Material	Copper
Surface protection	Tinned
Insulation	Other
Colour insulation	Blue
Type of connection	End connector

Packaging

00	
Inner Quantity	500
Inner Dimensions (inches)	6x5x4
Outer Quantity	2500
Outer Dimensions (inches)	26.5x6.5x4.5
Weight Uom	3.75 lbs. per 1000

Documents / Support Tools

Technical Drawing / Data Sheet US

Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Actual