

3000 SERIES

FLUSH MOUNTING LEXAN® HOUSING PHOTOCONTROL



Flush Mounting
Model 3010



APPLICATIONS

- Pole lanterns
- Lawn lighting
- Walkways

SPECIFICATIONS

ON/OFF: Turn ON is 1 to 5fc. Turn OFF is 3 to 15fc.

TIME DELAY: ON and OFF.

CELL: Cadmium sulphide, conformal coated 1/2" diameter.

CONTACTS: Normally closed (the unit fails in the ON position).

LEAD WIRES: Three color coded, minimum 9" wire leads, #16AWG, rated for 105 °C.

POWER CONSUMPTION:
Averages under 1 watt.

TEMPERATURE RANGE:
-40 °F to +158 °F (-40 °C to +70 °F).

FAIL MODE: ON.

WARRANTY: 5 years.

FEATURES

SENSOR: Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.

OPERATION: Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.

STANDARDS: Meets ANSI/UL773A.

HOUSING & MOUNTING: Control housing is weather-resistant molded Lexan® with ultrasonically welded seams.

MODEL 3000: Flush mounting through .6875" hole in post lantern or lighting fixture, 3/8" NPT, stem 3/4" long. Gasket and nut supplied.

MODEL 3010: flush mounting into standard, raintight junction box. Includes aluminum plate and gasket to fit FS type outdoor junction box.

ENERGY SAVINGS: Works with screw base CFLs.

CAT. NO.	UPC CODE	VOLTAGE (VAC) 50-60Hz	RATING		LED
			TUNGSTEN	BALLAST	
3000	60020	120	2000W	1800VA	600VA
3002	60019	208-277	3470-4620W	2080-2770VA	1040-1385VA
NEW! 3006	60026	347	5760W	3470VA	-
3010	60021	120	2000W	1800VA	600VA

*CSA certified only.

