

TURCK 7/8" minifast® Connectivity Products







5 and 6-Wire Cordsets, Heavy Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 600 V, 10 A (5-pin), 8 A (6-pin)



| Connector Style | Female Part Number | Male Part Number | Features | Pinout |
|------------------------|------------------------------------|------------------------------------|--|---|
| <p>RKM ..**</p> | RKM 55-*M WKM 55-*M | RSM 55-*M WSM 55-*M | STOW PVC Yellow, 5x16 AWG, 105°C, 13.2 mm OD, Cable #RF50540-*M†, flexlife* | 1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK |
| | RKM 55-*M/S600 WKM 55-*M/S600 | RSM 55-*M/S600 WSM 55-*M/S600 | SOOW CPE Yellow, 5x16 AWG, 105°C, 13 mm OD, Cable #RF50597-*M†, Weld Flash Immune, Flame Immune | 1. RD 2. RD 3. GN 4. RD 5. RD |
| <p>WKM ..**</p> | RKM 56-*M WKM 56-*M | RSM 56-*M WSM 56-*M | SEOW/STOW PVC Yellow, 5x16 AWG, 105°C, 13.2 mm OD, Cable #RF50539-*M†, flexlife | 1. WH 2. RD 3. GN 4. OG 5. BK |
| | RKM 56-*M/S1587 WKM 56-*M/S1587 | RSM 56-*M/S1587 WSM 56-*M/S1587 | SEOW/STOW TPE Yellow, 5x16 AWG, 105°C, 13.2 mm OD Cable #RF51265-*M†, weldlife, Weld Flash Immune | |
| <p>RSM ..**</p> | RKM 66-*M WKM 66-*M | RSM 66-*M WSM 66-*M | STOW PVC Yellow, 6x16 AWG, 105°C, 13.7 mm OD, Cable #RF50565-*M†, flexlife | 1. WH 2. RD 3. GN 4. OG 5. BK 6. BU |
| | RKM 66-*M/S1587 WKM 66-*M/S1587 | RSM 66-*M/S1587 WSM 66-*M/S1587 | SEOW/STOW TPE Yellow, 6x16 AWG, 105°C, 13.7 mm OD, Cable #RF51564-*M†, weldlife, Weld Flash Immune | |

Cordsets



* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RKM .."; "RK .." indicates nylon, "RKY .." indicates stainless steel, and "RKVH .." indicates stainless steel hex.
 † See Section N for **reelfast**® cable information.