



ø27.0 [1.06]⊣

CABLE LENGTH	TOLERANCE *					
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER					
STRIP LENGTH	TOLERANCE *					
0-7mm	±0.5mm					
8–29mm	±1.0mm					
30–49mm	±2.0mm					
50-69mm	±3.0mm					
70-100mm	±4.0mm					
OVER 100mm	±5.0mm					
* UNLESS OTHERWISE SPECIFIED						

## SOURCE DRAWING - FOR REFERENCE ONLY

RELATI	ED DOCUMENTS	3RD ANGLE PROJECTION	CONFIDE	DRAWING IS NTIAL AND THE TY OF TURCK				3000 CA MINNEAPOL	IS, MN	55441
2.			INC. U	JSE OF THIS		RC			-544-7 553-7	
3.				PERMISSION IS				(763)	553-0	708 fax
4.			PROHIBITED.					www.	.turck.u	IS
MATER	IIAL		DRFT	RWC	DATE 01/24/07	DESCRIPTION				
		ALL DIMENSIONS	APVD		SCALE	RSM 56-*M		-*M		
SE	E SPECIFICATIONS	DISPLAYED ON THIS DRAWING ARE FOR			SCALE 1=1.0					
			UNIT OF MEASUREMENT							
FINISH		REFERENCE ONLY		0.00	NOOTLEMENT	IDENTIFICATION NO.				REV
1 11131		CONTACT TURCK	L N	AILL IMPETE	ER[INCH]					
_		FOR MORE								E
SE	E SPECIFICATIONS	INFORMATION								
			DO NOT SCALE THIS DRAWING			FILE: 777003192			SHEET	1 OF 1

NOTES:

1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

		-				CONTACT TURCK FOR MORE	MILLIMETER [ INCH ]			F
E	UPDATE CONDUCTOR COLORS	NF	08/15/17	60457	SEE SPECIFICATIONS	INFORMATION				
REV	DESCRIPTION	BY	DATE	ECO NO.			DO NOT SCALE THIS DRAWING	FILE: 777003192	SHEET	1 OF
	-									