

## 3/8" DRIVE IMPACT SOCKETS - 6 POINT

- ▶ Proto® 6 Point Impact Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- ▶ Size stamped on tool for easy identification.
- ▶ Side locking hole.



- ▶ Radius-corner socket design
- ▶ Engages flats for better grip
- ▶ Improves the ability to turn worn or rounded fasteners

| INCH  | 6      | Nut End Outside Diameter (in) (B) | Drive End Outside Diameter (in) (C) | Nut Depth (in) (D) | Bolt Clearance Depth (in) (E) | Overall Length (in) (L) | Weight (lbs) |
|-------|--------|-----------------------------------|-------------------------------------|--------------------|-------------------------------|-------------------------|--------------|
| 1/4   | J7208H | 7/16                              | 11/16                               | 9/32               | 19/32                         | 1-3/32                  | 0.07         |
| 9/32  | J7209H | 31/64                             | 11/16                               | 5/16               | 19/32                         | 1-3/32                  | 0.07         |
| 5/16  | J7210H | 1/2                               | 11/16                               | 5/16               | 19/32                         | 1-3/32                  | 0.07         |
| 11/32 | J7211H | 35/64                             | 11/16                               | 3/8                | 19/32                         | 1-3/32                  | 0.07         |
| 3/8   | J7212H | 19/32                             | 11/16                               | 3/8                | 19/32                         | 1-3/32                  | 0.07         |
| 7/16  | J7214H | 11/16                             | 11/16                               | 3/8                | 19/32                         | 1-3/32                  | 0.06         |
| 1/2   | J7216H | 3/4                               | 3/4                                 | 3/8                | 19/32                         | 1-3/32                  | 0.08         |
| 9/16  | J7218H | 13/16                             | 13/16                               | 9/16               | 19/32                         | 1-3/32                  | 0.11         |
| 5/8   | J7220H | 29/32                             | 29/32                               | 9/16               | 19/32                         | 1-3/32                  | 0.12         |
| 11/16 | J7222H | 1                                 | 1                                   | 9/16               | 19/32                         | 1-3/32                  | 0.15         |
| 3/4   | J7224H | 1-1/16                            | 1-1/16                              | 17/32              | 19/32                         | 1-3/32                  | 0.16         |
| 13/16 | J7226H | 1-3/16                            | 1-13/64                             | 11/16              | 23/32                         | 1-7/32                  | 0.24         |
| 7/8   | J7228H | 1-9/32                            | 1-9/32                              | 11/16              | 23/32                         | 1-7/32                  | 0.26         |
| 15/16 | J7230H | 1-23/64                           | 1-23/64                             | 51/64              | 27/32                         | 1-11/32                 | 0.35         |
| 1     | J7232H | 1-1/2                             | 1-1/2                               | 51/64              | 27/32                         | 1-11/32                 | 0.42         |

ASME B107.2

| MM | 6      | Nut End Outside Diameter (in) (B) | Drive End Outside Diameter (in) (C) | Nut Depth (in) (D) | Bolt Clearance Depth (in) (E) | Overall Length (in) (L) | Weight (lbs) |
|----|--------|-----------------------------------|-------------------------------------|--------------------|-------------------------------|-------------------------|--------------|
| 6  | J7206M | 27/64                             | 11/16                               | 7/32               | 27/64                         | 59/64                   | 0.06         |
| 7  | J7207M | 31/64                             | 11/16                               | 15/64              | 27/64                         | 59/64                   | 0.06         |
| 8  | J7208M | 33/64                             | 11/16                               | 5/16               | 17/32                         | 1-1/32                  | 0.06         |
| 9  | J7209M | 37/64                             | 11/16                               | 11/32              | 17/32                         | 1-1/32                  | 0.06         |
| 10 | J7210M | 11/16                             | 11/16                               | 3/8                | 17/32                         | 1-1/32                  | 0.06         |
| 11 | J7211M | 11/16                             | 11/16                               | 13/32              | 17/32                         | 1-1/32                  | 0.06         |
| 12 | J7212M | 23/32                             | 23/32                               | 7/16               | 17/32                         | 1-1/32                  | 0.07         |
| 13 | J7213M | 3/4                               | 3/4                                 | 7/16               | 17/32                         | 1-3/32                  | 0.08         |
| 14 | J7214M | 13/16                             | 13/16                               | 9/16               | 19/32                         | 1-3/32                  | 0.09         |
| 15 | J7215M | 55/64                             | 55/64                               | 9/16               | 19/32                         | 1-3/32                  | 0.10         |
| 16 | J7216M | 29/32                             | 29/32                               | 9/16               | 19/32                         | 1-3/32                  | 0.12         |
| 17 | J7217M | 1                                 | 1                                   | 9/16               | 19/32                         | 1-3/32                  | 0.15         |
| 18 | J7218M | 1-1/32                            | 1-1/32                              | 9/16               | 19/32                         | 1-3/32                  | 0.16         |
| 19 | J7219M | 1-1/16                            | 1-1/16                              | 17/32              | 19/32                         | 1-3/32                  | 0.15         |
| 20 | J7220M | 1-7/64                            | 1-7/64                              | 17/32              | 19/32                         | 1-3/32                  | 0.18         |
| 21 | J7221M | 1-5/32                            | 1-5/32                              | 17/32              | 19/32                         | 1-3/32                  | 0.19         |
| 22 | J7222M | 1-13/64                           | 1-13/64                             | 17/32              | 19/32                         | 1-3/32                  | 0.20         |
| 23 | J7223M | 1-1/4                             | 1-1/4                               | 17/32              | 19/32                         | 1-3/32                  | 0.26         |
| 24 | J7224M | 1-19/64                           | 1-19/64                             | 17/32              | 19/32                         | 1-3/32                  | 0.27         |

ASME B107.33M