

Deburring intersecting oil passages in an engine block.



BORE-RX<sup>™</sup> CROSSHOLE DEBURRING BRUSHES

Designed for automated use in CNC machining centers and dedicated equipment. They are densely filled for high aggression and long tool life and feature a 3/8" diameter steel stem with a flat for use in a collet or end-mill holder.

Bore-Rx brushes are ideal tools for removing burrs from internal edges. Since they can eliminate manual deburring operations, these internal brushing tools help to improve part-to-part consistency and reduce direct labor costs. Bore-Rx brushes are available in sizes ranging from 3/4" to 4" in diameter, and they are designed to be interpolated within bore sizes that are larger than the brush diameter.

## **Operating Parameters For Wire Bore-Rx Brushes**

Brush Diameter	Recommended RPM	Recommended Feed Rate
5/8" - 7/8"	8,000	20"/min
1" - 1-1/2"	8,000	20"/min
2" - 2-1/2"	6,000	20"/min
3" - 4"	3,000	20"/min

### **Tool Paths for Crosshole Deburring**

An effective tool path for most crosshole deburring jobs is circular interpolation using the following guidelines to determine diameter of interpolation. The interpolation should be performed at a depth where the center of the brush face is at the center of the intersecting hole.

Diameter of Interpolation = Hole Diameter - Brush Diameter

## BORE-RX BRUSHING TOOLS - Crimped wire fill - Feature dense wire fill for aggressive

deburring action on ductile metals and other hard-to-deburr materials.

	Wire	Face	Overall	Max.	Standard	Item Number
Diameter	Size	Width	Length	RPM	Pack	Steel*
3/4"	.005	3/8"	4-3/8"	8,000	1	17202
		3/4"	4-3/4"			17203
7/8"	.006	3/4"	4-3/4"	8,000	1	17205
1"	.006	3/4"	5"	8,000	1	17207
1-1/4"	.006	3/4"	4-3/4"	8,000	1	17209
1-1/2"	.006	1"	5"	8,000	1	17211
2"	.006	1"	4-1/4"	6,000	1	17214
2-1/2"	.008	1"	4-3/4"	6,000	1	17216
3"	.008	1"	5-1/4"	6,000	1	17218
4"	.0118	1"	6-1/4"	6,000	1	17219



17205

\* Stainless Steel fill is available by special order

Note: All Bore-Rx brush stems have a 2" long flat for use in end mill holders. Alternatively, they can be mounted in 3/8" collets. Bore-Rx extension holder is available. Contact Application Engineering at 888-299-APPS (2777).

# **CUSTOMIZABLE CROSSHOLE DEBURRING SOLUTIONS**

### **Replacement Bore-Rx Brush Heads and Reusable Bore-Rx Arbors**

In high production applications, reusable arbors reduce manufacturing costs by allowing the use of inexpensive brush head replacements. Brush heads are made-to-order in diameters ranging from 3/4" to 1-1/2" with face widths of 1/4" to 1". They are available on 3/16" and 1/4" pins. The pin diameter is based on the application and determines brush density. Contact Application Engineering at 888-299-APPS (2777) for more information.









17218