
P

BURRITE - Feature a single continuous length of stainless steel stem wire and filled with a tuft of crimped wire to provide an aggressive flat side action; ideal for cleaning and deburring internal threads.



Diameter	Wire Size	Brush Part	Stem Diameter	Overall Length	Max. RPM	Standard Pack	Item Number	
							Steel	Stainless
1/4"	.003	9/16"	3/32"	2-1/8"	2,000	10	21000	_
	.005						21001	21050
5/16"	.003	9/16"	3/32"	2-1/8"	2,000	10	21004	_
	.005						21005	_
3/8"	.003	9/16"	3/32"	2-1/8"	2,000	10	21008	_
	.005						21009	21051
	.005		1/8"				21023	_
7/16"	.003	9/16"	3/32"	2-1/8"	2,000	10	21014	_
	.005						21015	_
1/2"	.003	9/16"	3/32"	2-1/8"	2,000	10	21020	_
	.005						21021	21053
	.005		1/8"				21025	_
9/16"	.003	5/8"	1/8"	2-1/4"	2,000	10	21027	_
	.005						21028	_
5/8"	.003	5/8"	1/8"	2-1/4"	2,000	10	21030	_
	.005						21031	21055
3/4"	.005	5/8"	1/8"	2-1/4"	2,000	10	21034	21056
	.008						21035	_
7/8"	.005	5/8"	1/8"	2-1/4"	2,000	10	21036	21057
1"	.005	5/8"	1/8"	2-1/4"	2,000	10	21040	21058
	.008						21041	_
1-1/8"	.005	5/8"	1/8"	2-1/4"	2,000	10	21044	_



Deburring the threads of a tapped hole using a burrite brush in a holder.





BURRITE HOLDERS - Feature a 1/4" stem for convenient mounting into the chuck of a drill or the collet of a machine tool and allow the brush to be used in either direction of rotation. They allow the brush to be used in a standard tapping cycle for deburring threaded holes in CNC machining centers.



For Brush Stem Dia.	Holder Diameter	Overall Length	Standard Pack	Item Number
3/32"	1/4"	3-1/8"	5	95202
1/8"	3/8"	3-3/8"	5	95203



SINGLE STEM, SINGLE SPIRAL - Feature a single continuous length of galvanized steel stem wire with a formed eye loop for convenient hand use. The single spiral of straight wire fill allows for easy manual insertion into the ID.

	Wire	Brush	Stem	Overall Length	Standard Pack	Item Number	
Diameter	Size	Part	Diameter			Steel	Stainless
1/8"	.003	1"	3/32"	6"	10	21246	21249
3/16"	.003	1-1/2"	3/32"	7"	10	21090 🔺	21098
	.005					21091	21099
1/4"	.003	1-1/2"	3/32"	7"	10	21092 🔺	21100
	.005					21093 🔺	21101
	.006					21161	_
3/8"	.004	2"	1/8"	8"	10	21094 🔺	21414
	.006					21095	21103
1/2"	.004	2"	1/8"	8"	10	21096 🔺	21104
	.006					21097	21105
	.008					21162	-
9/16"	.005	2-1/2"	5/32"	9"	10	21233	

▲ Available in non-sparking brass wire, see page 88-89 for details.







