

Removing gasket material from a pipe flange.



31112



86160



86148







#### NOTE

Nylon abrasive filament brushes require a lower operating RPM than most other power tool accessories and they cannot be used effectively on standard grinders.

# **FME AREA PRODUCT SOLUTIONS**

In nuclear power plants, Foreign Material Exclusion (FME) programs may limit or even exclude the use of wire brushes in some areas during the performance of routine maintenance, repair or shutdown activities. Weiler has developed a FME-compliant tooling system to address the needs of plant operators and maintenance contractors working in these facilities as well as other industries where the potential introduction of broken wire filaments may be of concern. Weiler's FME Solutions program is a complete system consisting of non-wire brushing tools designed to perform a broad range of surface cleaning and preparation applications.

**BLACK NYLOX® CERAMIC BRUSHES** - The engineered ceramic grain in Weiler's Black Nylox filament is up to 400% more aggressive than the silicon carbide and aluminum oxide grain in other abrasive filaments, making it much more effective in surface cleaning applications. The efficient cutting action of the Black Nylox filament also generates less heat and makes it much more resistant to "smearing" than traditional nylon abrasive filaments.

## NARROW FACE WHEELS - Crimped Ceramic Filament

Used on edge for weld prep and cold weld cleaning.							
Diameter	Filament Dia./Grit	Face Width	Arbor Hole	Max. RPM	Standard Pack	ltem Number	
4"	.055/80	1/2"	5/8"-11 Nut	4,800	5	31112	
4"	.043/120	1/2"	5/8"-11 Nut	4,800	5	31111	

**CUP BRUSH -** Rectangular Ceramic Filament Used on its face for beaw-duty cleaning of broad surfaces

0000 01110 1000	<u> </u>				
Diameter	Filament Dia./Grit	Arbor Hole	Max. RPM	Standard Pack	ltem Number
4"	.049 x .098 - 80 Grit	5/8"-11 Nut	4,800	1	86160

50-2

**END BRUSH -** Crimped Ceramic Filament - 1/4" Stem For spot-facing or cleaning in tight areas

For spot-facing or cleaning in tight areas.								
Diameter	Filament Dia./Grit	Trim Length	Overall Length	Max. RPM	Standard Pack	ltem Number		
1"	.055/80	1/4"	3-3/32"	4,800	10	86148		

#### CONTROLLED FLARE END BRUSH - Crimped Ceramic Filament - 1/4" Stem

For cleaning corners and tight areas.

Diameter	Filament	Trim	Overall	Max.	Standard	ltem
	Dia./Grit	Length	Length	RPM	Pack	Number
1"	.035/80	1-1/8"	2-1/2"	4,800	10	86159

#### **CONFLEX BRUSHES** - Crimped Ceramic Filament - 1/4" Stem For 0.D. and I.D. cleaning in confined areas.

U.L	. and i.d. cleaning in comme			
	Filament	Face	Trim	

	Filament	Face	Trim	Max.	Standard	ltem
Diameter	Dia./Grit	Width	Length	RPM	Pack	Number
3"	.043/120	1"	15/16"	4,800	10	86171
3"	.055/80	1"	15/16"	4,800	10	86172

### HAND SCRATCH BRUSHES - Crimped Ceramic Filament - For general purpose, light-duty cleaning.

		e on inpour o		i of gonoral parpooo, light daty oroannig.			
Overall Length	Block Type	Brush Part	Grit Size	Trim Length	Standard Pack	ltem Number	
10"	Wood	5"	80	3/4"	12	44144	
8-3/4"	Wood	2 x 9 Rows	120	5/8"	36	95016	