

Removing burrs from the inside diameter of a cut tube.



52027



52621



53286

NOTE

Р

COATED ABRASIVE FLAP WHEELS



Weiler's abrasive flap wheels are designed with a solid hub construction that enables wheels to be rated at higher RPMs and provide more aggressive cutting action and increased productivity. They provide perfect balance leading to smooth, chatter-free finishing.

Applications

- Internal diameter cleaning
- Finishing metal surfaces
- Deburring machined parts
- · Cleaning and reconditioning pipe threads

Tiger Mounted Flap Wheels - 1/4" Stem - Aluminum Oxide

- Polishing, blending & finishing
- Prepping surface for painting or plating
- Edge blending



Diameter	Width	Grit Size	Max. RPM	Standard Pack	Item Numbe
1"	1"	60	30,000	10	52003
		80			52004
		120			52005
1-1/2"	1"	60	25,000	10	52009
		80			52010
		120			52011
2"	1/2"	60	25,000	10	52366
		80			52367
2"	1"	60	25,000	10	52015
		80			52016
		120			52017
2-1/2"	1"	60	23,000	10	52486
		80			52487
3"	1/2"	60	23,000	10	52024
		80			52025
3"	1"	60	23,000	10	52027
		80			52028
		120			52029





Diameter	Width	Grit Size	Max. RPM	Standard Pack	Item Number
1"	1"	60	30,000	10	52601
		80			52603
		120			52605
2"	1"	60	25,000	10	52611
		80			52613
3"	1"	60	20,000	10	52621
		80			52623

TIGER® UNMOUNTED FLAP WHEELS - Aluminum Oxide P



Value line

Professional Grade

Diameter	Width	Arbor Hole	Grit Size	Max. RPM	Standard Pack	Item Number
6"	1"	1"	60	6,000	5	53286
			80			53287
6"	2"	1"	60	5,700	3	53326
			80			53327

Key:

P

Performance line

Industrial Grade

Drive arbor is used individually and must be ordered individually.
Drive arbor is to be used with Weiler flap wheels only.

· Stems must be fully chucked before using and should not be run above the maximum RPM listed.