

V VORTEC PRO® SMALL CUTTING WHEELS Reinforced (Type 1)

General purpose cutting applications in tool rooms and machine shops.



Diameter	Wheel Thickness	Arbor Hole	Type	Max. RPM	Std. Pack	Item Number
						Aluminum Oxide
2"	.035"	1/4"	WA60T - Metal	30,000	100	56013*
	1/16"	1/4"	A36T - Metal			56015
	1/4"	3/8"	A36T - Metal			56131
3"	.035"	1/4"	WA60T - Metal	25,000	100	56061*
	.035"	3/8"	WA60T - Metal			56062*
	1/16"	1/4"	A36T - Metal			56065
	1/16"	3/8"	A36T - Metal			56068
	1/8"	3/8"	A36T - Metal			56076
	1/8"	1/4"	A36T - Metal			56270
4"	.035"	5/8"	WA60T - Metal	19,000	50	56271*
	.035"	3/8"	WA60T - Metal			56080*
	1/16"	3/8"	A36T - Metal			56086
	1/4"	3/8"	A36T - Metal			56163
	1/8"	3/8"	A36T - Metal			56099
4-1/2"	.045"	7/8"	WA60T - Metal	13,500	50	56281*
	1/16"	7/8"	A60T - Metal			56103
5"	.035"	5/8"	WA60T - Metal	12,200	100	56108*
	1/16"	7/8"	A36T - Metal			56118

*Contaminant-free.



56013



56103



56282

V VORTEC PRO® THIN CUTTING WHEELS Reinforced (Type 1)

General purpose metal applications in tool rooms and machine shops.



Diameter	Wheel Thickness	Arbor Hole	Type	Max. RPM	Std. Pack	Item Number
						Aluminum Oxide
6"	.040"	7/8"	WA60T - Metal	10,200	25	56282*
	.045"	7/8"	WA60T - Metal			56273*
7"	.045"	7/8"	WA60T - Metal	8,740	25	56275*

*Contaminant-free.

DIA. = 5/8" arbor with diamond knockout adapter for circular saws.

MOUNTING MANDRELS 1/4" Stem. For Type 1 wheels only.

Arbor Size	Wheel Thickness	Standard Pack	Item Number
1/4"	.035" to 1/4"	10	56489
3/8"	.035" to 1/4"	10	56490
1/4", 3/8" *	.035" to 1/4"	10	56491*
1/4", 3/8"+	.035" to 1/4"	1	36512+

*Combination pack +Display packaged



56489

Key:

P PERFORMANCE LINE Industrial Grade **V** VALUE LINE Professional Grade

WHY WEILER

COATED ABRASIVES

BONDED ABRASIVES

BRUSHES