CUTTING WHEELS



Cutting a piece of Steel tubing to length.

For general purpose cutting applications on Steel, Iron, and other ferrous metals. Formulated for aggressive stock removal and fast cutting and reinforced with fiberglass webbing for stability.

APPLICATIONS

- Weld removal
- Cutting and parting
- Notching





THIN CUTTING WHEELS Depressed Center (Type 27)

For fast, burr-free cutting with longer life and less resistance on various metals.

| | Wheel | | | | | Item Number |
|----------|-----------|------------|--------------|----------|-----------|------------------|
| Diameter | Thickness | Arbor Hole | Туре | Max. RPM | Std. Pack | Zirconia Alumina |
| 4-1/2" | .045" | 7/8" | Z46T - Metal | 13,300 | 25 | 56389 |
| 5" | .045" | 7/8" | Z46T - Metal | 12,200 | 50 | 56388 |
| 7" | .060" | 7/8" | Z36T - Metal | 8,500 | 25 | 56387 |





VORTEC PRO® THIN CUTTING WHEELS Depressed Center (Type 27)

For general purpose, burr-free cutting with less resistance on various metals.

| | Wheel | | | | | Item Number |
|----------|-----------|------------|---------------|----------|-----------|----------------|
| Diameter | Thickness | Arbor Hole | Туре | Max. RPM | Std. Pack | Aluminum Oxide |
| 4-1/2" | .045" | 7/8" | WA60S - Metal | 13,300 | 25 | 56393* |
| 5" | .045" | 7/8" | WA60S - Metal | 12,200 | 100 | 56392* |
| 6" | .045" | 7/8" | WA60S - Metal | 10,200 | 25 | 56283* |
| 7" | .060" | 7/8" | WA60S - Metal | 8,500 | 25 | 56391* |

^{*}Contaminant-free.





VORTEC PRO® CUTTING WHEELS Depressed Center (Type 27)

For general purpose cutting on ferrous metals.

| | Wheel | | | | | Item Number |
|----------|-----------|------------|--------------|----------|-----------|----------------|
| Diameter | Thickness | Arbor Hole | Туре | Max. RPM | Std. Pack | Aluminum Oxide |
| 4" | 3/32" | 5/8" | A24T - Metal | 15,200 | 25 | 56474 |
| 4-1/2" | 3/32" | 5/8"-11 | A24T - Metal | 13,300 | 10 | 56385 |
| | | 7/8" | | | 25 | 56475 |
| 5″ | 3/32" | 5/8"-11 | A24T - Metal | 12,200 | 10 | 56384 |
| | | 7/8" | | | 25 | 56476 |
| 6" | 3/32" | 5/8"-11 | A24R - Metal | 10,200 | 10 | 56278 |
| | | 7/8" | | | 25 | 56277 |
| 7" | 3/32" | 5/8"-11 | A24R - Metal | 8,500 | 10 | 56477 |
| | | 7/8" | | | 25 | 56383 |



56430

VORTEC PRO® CUTTING & NOTCHING WHEELS Depressed Center (Type 27)

General purpose light grinding and cutting. For root pass cutting and light grinding.



