



Standard Corrugated Vinyl

Group 381

Our most popular runner, Standard Corrugated Vinyl protects floors, reduces cleaning costs and adds traction where it's needed.

- Protects floors, 1/8" (3 mm) thick
- Easy to clean, chemical resistant surface
- Vinyl compound won't curl during use

www.wearwell.com

Type	Runner
Suitable Environment	Dry
Customization Level	C1 - Custom Length
Solid or Drainage	Solid
Compound	PVC
Recycled	>50%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1% lost @ 1,000 cycles
Temperature Range	-10 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .91 / Wet: COF = .65
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

Part Number	UPC	Color	Thickness	Dimensions	Stock Part	UOM
381.18x2x105BK	715411502929	Black	0.125	2' x 105'	Y	RL
381.18x2x150BK	715411502806	Black	0.125	2' x 150'	Y	RL
381.18x2x75BK	715411429219	Black	0.125	2' x 75'	Y	RL
381.18x3x105BK	715411503223	Black	0.125	3' x 105'	Y	RL
381.18x3x150BK	715411503100	Black	0.125	3' x 150'	Y	RL
381.18x3x75BK	715411429226	Black	0.125	3' x 75'	Y	RL
381.18x4x105BK	715411503520	Black	0.125	4' x 105'	Y	RL
381.18x4x150BK	715411503407	Black	0.125	4' x 150'	Y	RL
381.18x4x75BK	715411429233	Black	0.125	4' x 75'	Y	RL
381.18x2CUTBK	715411502684	Black	1/8	2' Cut up to 150'	N	SF
381.18x3CUTBK	715411502981	Black	1/8	3' Cut up to 150'	N	SF
381.18x4CUTBK	715411503285	Black	1/8	4' Cut up to 150'	N	SF

