

**NEW NAME, SAME GREAT QUALITY**

**DEPENDABLE.  
DOMESTIC.**

**DURAGUARD™**  
**RIGID METAL CONDUIT.**

MADE AND  
MELTED IN **AMERICA**

**Ready to ship**

Trade sizes ½-6

10' & exclusive 20' lengths

Coupling supplied  
on one end

**Guaranteed 100% Made & Melted in America**

DuraGuard provides the ultimate physical protection for conductors. Its thick walls and hot-dip galvanization ensure long-lasting performance. And because DuraGuard is manufactured right here in the heartland, it's guaranteed to meet the strictest American-made standards and NECA codes.

**Get the DuraGuard brochure and stocking info**  
from Wheatland Tube, America's leading producer of rigid metal conduit.  
[wheatland.com/duraguard](http://wheatland.com/duraguard) | 800.257.8182



**Wheatland Tube**

JMC STEEL GROUP

# DuraGuard™ Rigid Metal Conduit: The ultimate protection



With thick walls and hot-dip galvanized OD and ID, DuraGuard ensures long-lasting performance.

## DURAGUARD WEIGHTS AND DIMENSIONS (10' AND 20' LENGTHS)

TRADE SIZE	METRIC DESIGNATOR	THREADS/ INCH	WEIGHT PER 100 FT.		NOMINAL OUTSIDE DIAMETER		NOMINAL INSIDE DIAMETER	
			lbs.	kg	in.	mm	in.	mm
½	16	14	82	37.2	0.840	21.34	0.632	16.05
¾	21	14	109	49.4	1.050	26.67	0.836	21.23
1	27	11½	161	73.0	1.315	33.40	1.063	27.00
1¼	35	11½	218	98.9	1.660	42.16	1.394	35.41
1½	41	11½	263	119.3	1.900	48.26	1.624	41.25
2	53	11½	350	158.8	2.375	60.33	2.083	52.91
2½	63	8	559	253.6	2.875	73.03	2.489	63.22
3	78	8	727	329.8	3.500	88.90	3.090	78.49
3½	91	8	880	399.2	4.000	101.60	3.570	90.68
4	103	8	1030	467.2	4.500	114.30	4.050	102.87
5	129	8	1400	635.0	5.563	141.30	5.073	128.85
6	155	8	1840	834.6	6.625	168.28	6.093	154.76

Applicable tolerances: Outside Diameter ½-1½: ±0.015" (16-41: ±0.38 mm), 2-6: (53-155) ± 1%.

## PACKAGING (10' LENGTHS)

TRADE SIZE	METRIC DESIGNATOR	THREAD PROTECTOR COLOR	QUANTITY / BUNDLE			QUANTITY / LIFT*				WEIGHT / LIFT		VOLUME / LIFT	
			ft.	m	Pieces	Bundles	ft.	m	lbs.	kg	cu. ft.	cu. m	
½	16	Black	100	30.5	—	25	2500	762	2050	929.9	19.4	0.6	
¾	21	Red	50	15.2	—	40	2000	610	2180	988.8	26.7	0.8	
1	27	Blue	50	15.2	—	25	1250	381	2013	913.1	22.2	0.6	
1¼	35	Red	—	—	90	—	900	274	1962	889.9	28.3	0.8	
1½	41	Black	—	—	80	—	800	244	2104	954.4	27.2	0.8	
2	53	Blue	—	—	60	—	600	183	2100	952.5	36.1	1.0	
2½	63	Black	—	—	37	—	370	113	2068	938.0	35.0	1.0	
3	78	Blue	—	—	30	—	300	91	2181	989.3	41.5	1.2	
3½	91	Black	—	—	25	—	250	76	2200	997.9	43.3	1.2	
4	103	Blue	—	—	20	—	200	61	2060	934.4	48.6	1.4	
5	129	Blue	—	—	15	—	150	46	2100	952.5	52.1	1.5	
6	155	Blue	—	—	10	—	100	30	1840	834.6	43.8	1.2	

\* The quantity per lift conforms to the National Electrical Manufacturers Association Standards Publication RN-2 Packaging of Master Bundles for Steel Rigid Metal Conduit, Intermediate Metal Conduit (IMC) and Electrical Metallic Tubing (EMT).  
Pack quantities for Canadian distribution does not comply with NEMA RN-2.

## PACKAGING (20' LENGTHS)

TRADE SIZE	METRIC DESIGNATOR	THREAD PROTECTOR COLOR	QUANTITY / LIFT			WEIGHT / LIFT		VOLUME / LIFT	
			Pieces	ft.	m	lbs.	kg	cu. ft.	cu. m
½	16	Black	125	2500	762	2050	929.9	13.9	0.4
¾	21	Red	100	2000	610	2180	988.8	20.0	0.6
1	27	Blue	60	1200	366	1932	876.4	17.5	0.5
1¼	35	Red	45	900	274	1962	890.0	19.4	0.5
1½	41	Black	40	800	244	2104	954.4	18.7	0.5
2	53	Blue	30	600	183	2100	952.6	29.6	0.8
2½	63	Black	18	360	110	2012	912.6	23.4	0.7
3	78	Blue	15	300	91	2181	989.3	28.0	0.8
3½	91	Black	12	240	73	2112	958.0	32.2	0.9
4	103	Blue	10	200	61	2060	934.4	30.8	0.9
5	129	Blue	7	140	43	1960	889.1	35.0	1.0
6	155	Blue	5	100	30	1840	834.6	34.3	1.0

The length is nominal and subject to the tolerance of UL Standard for Safety for Electrical Rigid Metal Conduit—Steel, UL-6.