



Including Wheatland Tube, Atlas Tube and Picoma Industries

JMC Steel Group Corporate Office

227 West Monroe Street
 26th Floor
 Chicago, IL 60606
 Phone: (312) 275-1601

Wheatland Tube Divisional Office

700 South Dock Street
 Sharon, Pennsylvania 16146
 Phone: (800) 257-8182
 (724) 342-6851

<p><u>Council Plant</u></p> <p>One Council Avenue Wheatland, Pennsylvania 16161 Phone: (724) 342-6851</p> <p><i>Mailing Address:</i> PO Box 608 Wheatland, Pennsylvania 16161</p>	<p><u>Mill Street – Cold Draw Plant</u></p> <p>134 Mill Street Sharon, Pennsylvania 16146 Phone: (724) 342-6851</p>
<p><u>Church Street – Cold Draw Plant</u></p> <p>20 Church Street Wheatland, Pennsylvania 16161 Phone: (724) 342-6851</p>	<p><u>Niles Plant</u></p> <p>1800 Hunter Street Niles, Ohio 44446 Phone: (330) 544-3408</p>
<p><u>Warren Plant</u></p> <p>901 Dietz Road NE Warren, Ohio 44483-2700 Phone: (330) 372-6611</p>	<p><u>Chicago Plant</u></p> <p>4435 South Western Boulevard Chicago, Illinois 60609-3024 Phone: (773) 254-0617</p>
<p><u>Picoma Industries</u></p> <p>9208 Jeffrey Drive Cambridge, Ohio 43725 Phone: (740) 432-2146</p>	



Atlas Tube Divisional Office

1855 East 122nd Street
 Chicago, Illinois 60633
 Phone: (800) 773-5683

<p><u>Chicago Plant</u></p> <p>1855 East 122nd Street Chicago, Illinois 60633 Phone: (800) 773-5683</p>	<p><u>Plymouth Plant</u></p> <p>13101 Eckles Road Plymouth, Michigan 48170-4245 Phone: (734) 738-5600 (888) 783-8823</p>
<p><u>Harrow Plant</u></p> <p>200 Clark Street Harrow, Ontario N0R 1G0 Canada Phone: (519) 738-5000 (800) 265-6912</p>	



Dear Customer:

Enclosed is a JMC Steel Group Material Safety Data Sheet for the pipe and conduit products that you purchase. It is the continuing policy of JMC Steel Group to provide to our customers, health, safety and environmental protection information that is appropriate for handling and utilizing our products.

These Material Safety Data Sheets contain information that is valuable to your employee health and safety program and may be required to be in your possession by the Federal OSHA Hazard Communication Standard or other right-to-know legislation. It is important that your facility hazard communication coordinator, industrial hygiene or safety personnel receives this information so that it can be communicated to those employees having contact with these products.

A revised Material Safety Data Sheet will be forwarded to you when significant changes of the information contained therein necessitate publication of an updated copy.

Addendum 2 lists the most commonly used rust preventative or protective coatings that are applied to products requiring such treatment, if a coating is not specified by you. This addendum is available upon request. This addendum lists the coatings which are applied and the manufacturer's identification and address. This information will be provided to enable you to obtain a Material Safety Data Sheet directly from the manufacturer or supplier for the rust preventative or coating that is applied to the product that you purchase. Material Safety Data Sheets for specified coatings should also be requested from the manufacturer or supplier of the coating. This procedure will make it possible for the manufacturer or supplier to send copies of Material Safety Data Sheets directly to you, as a user of that product, when revised MSDS'S are produced.

Also contained in the package is a label that can be reproduced or the information contained therein extracted for label-producing purposes.

Hazard Communication Programs are of the utmost importance to JMC Steel Group. We believe this information will be very beneficial to your Hazard Communication Program and we welcome any inquiries regarding additional information that you may require.

GREG MAURER
DIRECTOR TECHNICAL SERVICES AND QUALITY ASSURANCE
Direct Line (724) 983-2541
Cell (501) 352-1948
Fax (724) 342 0294



**JMC STEEL GROUP
MATERIAL SAFETY DATA SHEET**

Original Issue Date: 11/01/85

MSDS #268

Revision Date:	06/05/90 #2	02/05/99 #5	09/26/03 #8	12/19/05 #11
	08/24/92 #3	06/28/99 #6	04/13/05 #9	10/05/07 #12
	06/15/95 #4	11/08/01 #7	09/21/05 #10	03/11/11 #13

EMERGENCY TELEPHONE NUMBER	Main Plant	(724) 342-6851
CONTACT: Gregory L. Maurer	Office Direct	(724) 983-2541

I. IDENTIFICATION

PRODUCT NAME: CBW Pipe-ERW Pipe-Carbon Steel, ASTM STANDARD A53, A135, A501, A513, A589, A733, A795, A618, A865, F1043, F1083, API STANDARD 5A, 5L, A106, UL STANDARD 6, 797, 1242, Wheatland Product MLT, MEGA-FLOW, MEGA-THREAD, WLS, WST, GL, WT-40, WT-30, WT-20

COMMON NAMES: Standard Pipe, Schedule 40, Fence Pipe, Mechanical Tubing and Pipe, Schedule 10, Plumbing Pipe, Sprinkler Pipe, Water Pipe, Line Pipe, Gas Pipe, Steam Pipe, Extra Heavy Pipe, Schedule 80, R & D, Rigid Conduit, EMT, IMC, Couplings, Fittings, Nipples and Coupling Stock.

CAS NO. 65997-19-5

Manufacturer: Listed above



**JMC STEEL GROUP
MATERIAL SAFETY DATA SHEET**

II. INGREDIENTS AND RECOMMENDED OCCUPATIONAL EXPOSURE LIMITS

Note: steel products under normal conditions do not present an inhalation, ingestion, or contact health hazard (see section VI).

BASE METAL, ALLOYING ELEMENTS AND METAL COATINGS	% WEIGHT	EXPOSURE OSHA PEL	LIMITS ACGIH TLV
Base Metal: Iron (1309-37-1 as iron-oxide fume)	98-99	10 mg/M ³ for iron oxide fume	5 mg/M ³ for iron oxide fume
Alloying Elements:			
Carbon (7440-44-0)	0.02 - .25	15 mg/M ³ -total dust PNOR 5 mg/M ³ RF - PNOR	None Established
Manganese (7439-96-5)	0.15 - 1.40	(c) 5 mg/M ³	0.2 mg/M ³
Phosphorus (7723-14-0)	0.010 - .080	None for inorganic phosphates	None for inorganic phosphates
Sulfur as SO ₂ (7446-09-5)	0.005 - .120	13 mg/M ³	5.2 mg/M ³ 13 mg/M ³ (s)
Copper (7440-50-8)	< .15	1.0 mg/M ³ -dust, 0.1 mg/M ³ fume	1.0 mg/M ³ dust, 0.2 mg/M ³ - fume
Nickel (7440-02-0)	< .12	1.0 mg/M ³	0.2 mg/M ³ insoluble inorganic compounds
Chromium (7440-47-3)	< .12	1.0 mg/M ³	0.05 mg/M ³
Vanadium as V ₂ O ₅ (1314-62-1)	< .10	0.05 mg/M ³ - dust (c) 0.1 mg/M ³ - fume	(c) 0.05 mg/M ³ - dust, (c) 0.05 mg/M ³ - fume
Metallic Coating*			
Zinc (1314-13-2 as zinc oxide)	.070-6.0	15 mg/M ³ -total ZnO dust 5 mg/M ³ Respirable ZnO Dust & fume 5 mg/M ³	10 mg/M ³ -total ZnO dust 2 mg/M ³ Respirable ZnO Dust & fume (s) 10 mg/M ³

(c) Denotes “ceiling limit” which is not to be exceeded at any time

(s) Denotes Short Term Exposure Limit (STEL)

RF denotes Respirable Fraction

PNOR – Particulates Not Otherwise Regulated

Varnish coating may be used; See Addendum II

*Galvanized pipe only.

NOTE: All commercial metals contain small amounts of various elements in addition to those specified. These small quantities, frequently referred to as “trace” or “residual” elements, generally originate in the raw materials used.



**JMC STEEL GROUP
MATERIAL SAFETY DATA SHEET**

III. PHYSICAL DATA

MELTING POINT		Appearance and Odor:
Base Metal:	2750 F	Metallic Gray
Metallic Coating:	800-900F	No Odor

IV. FIRE AND EXPLOSION HAZARD DATA

Steel products in the solid state present no fire or explosion hazard and do not contribute to the combustion of other products.

V. REACTIVITY DATA

Stable under normal conditions of use, storage and transport. Will react with strong acid to liberate hydrogen. At temperatures above the melting point of the coating, galvanized pipe may liberate zinc fumes.

VI. HEALTH HAZARD DATA

HMIS CODE: H = 1, F = 0, R = 0

NOTE: Steel products under normal conditions do not present an inhalation, ingestion, or contact health hazard. However, operations such as burning, welding, sawing, brazing, grinding, and possibly machining, etc., which result in elevating the temperature of the product to or above its melting point or results in the generation of airborne particulate, may present health hazards.

EFFECTS OF OVEREXPOSURE

**MAJOR EXPOSURE HAZARD
INHALATION**

Chronic inhalation of high concentration of iron oxide fumes or dusts may lead to a benign pneumoconiosis. Inhalation of high concentrations of ferric oxide may possibly enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens.

The inhalation of high concentrations of freshly formed oxide fumes and dusts of Manganese, Copper, Lead and/or Zinc in the respirable particle size range can cause an influenza-like illness termed metal fume fever. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in the mouth, dryness and irritation in the throat, followed by weakness, muscle pain, fever and chills.

EMERGENCY AND FIRST AID PROCEDURES

For overexposure to airborne fumes and particulate, remove exposed person to fresh air. If breathing is difficult or has stopped, administer artificial respiration or oxygen as indicated. Seek medical attention promptly. Treat metal fume fever by bed rest and administer a pain and fever reducing medication. Seek medical attention.

VII. SPILL OR LEAK PROCEDURES

NOT APPLICABLE TO STEEL IN THE SOLID STATE.



**JMC STEEL GROUP
MATERIAL SAFETY DATA SHEET**

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY

NIOSH/MSHA-approved dust and fume respirators should be used to avoid excessive inhalation of particulate. Appropriate respirator selection depends on the magnitude of exposure.

SKIN:

Protective gloves should be worn as required for welding, burning, or handling operations.

EYE:

Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding, or machining operations.

VENTILATION:

Local exhaust ventilation should be provided when welding, burning, sawing, brazing, grinding, or machining to prevent excessive dust or fume exposure.

OTHER PROTECTIVE EQUIPMENT:

Depending upon the conditions of use and specific work situations, additional protective equipment and/or clothing may be required to control exposures.

IX. SPECIAL PRECAUTIONS

Operations with the potential for generating high concentrations of airborne particulate should be evaluated and controlled as necessary. Avoid breathing metal fumes and/or dusts.

OTHER COMMENTS:

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: individuals with chronic respiratory disorders (i.e.: asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.

This information is taken from sources or based upon data believed to be reliable; however, Wheatland Tube Company makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.



**JMC STEEL GROUP
MATERIAL SAFETY DATA SHEET**

ADDENDUM 1

In compliance with U.S. Environmental Protection Agency regulations that became effective on January 1, 1989, this addendum is to inform you that the products covered by our Material Safety Data Sheet #268 contains one or more of the below listed chemicals that are subject to reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Manganese Zinc Nickel

Refer to Addendum 2 of the Material Safety Data Sheet for the CAS numbers and percent by weight for each of the chemicals listed.

Addendum 2 lists the most commonly used rust preventative or protective coatings that are applied to products requiring such treatment, if a coating is not specified by you. This addendum is available upon request from:

GREG MAURER
DIRECTOR TECHNICAL SERVICES AND QUALITY ASSURANCE
Direct Line (724) 983 2541
Cell (501) 352-1948
Fax (724) 342-0294

The above referenced law requires certain manufacturers to report annual emissions of specified toxic chemicals and chemical categories. If you are unsure if you must report or, if you require more information, call the EPA Emergency Planning and Community Right-To-Know Hotline (800)535-0202 or (202)479-2449 (in Washington, DC or Alaska).