

## Wiha Adjustable TorqueControl Tools

### Wiha TorqueControl Screwdrivers

- TorqueFix factory preset torque
- TorqueVario adjustable torque drivers

*molded cushion grip two component handles allow for maximum achievable torque to be reached with comfort.*

**Precise repeatability!**

**All TorqueFix & TorqueVario tools are tested and comply with:**

- EN ISO 6798
- BS EN 26789
- ASME B107.14M

**Each tool has unique serial number and certificate of calibration**

Whether it's TorqueVario-S or TorqueFix - Wiha has a torque screwdriver to cover almost every application



#### 285 TorqueFix, With Wiha-SoftFinish® Handle

Fixed Torque value pre-set. Tested in accordance with EN ISO 6798, BS EN 26789, ASME B107.14M, tolerance +/- 6%. Audible and perceptible click when pre-set torque has been attained.

Automatically resets for next torque cycle; 50% greater reverse torque.

Item No.	Pre-Sets						
	oz.	lbs.	Nm	mm	Inch	lbs.	pkg.
28503	80	5	0.56	112	4.4	.16	1
28505	120	7.5	0.84	112	4.4	.15	1
28507	160	10	1.12	119	4.7	.28	1
28509	200	12.5	1.41	119	4.7	.27	1
28511	240	15	1.69	119	4.7	.27	1
28513	320	20	2.25	119	4.7	.28	1
28515	400	25	2.82	126	4.9	.37	1
28517	480	30	3.39	126	4.9	.37	1
28518	560	35	3.95	126	4.9	.37	1
28519	640	40	4.52	126	4.9	.37	1
28521	800	50	5.65	132	5.2	.52	1
28523	960	60	6.78	132	5.2	.52	1
28525	1120	70	7.91	132	5.2	.52	1

#### 285 Adjustable TorqueVario With Direct Reading Scale

EN ISO 6798, BS EN 26789, ASME B107.14M. Ergonomic molded multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when the torque setting has been attained, automatically resets for next torque cycle.

Item No.	Range					
	Inch	lbs.	Increments	mm	lbs.	
28501*	15 - 80	(in/oz)	2.5 Inch oz	122 - 127	.22	1
28502	5 - 10		.5 Inch lbs	122 - 127	.41	1
28504	7.5 - 20		.5 Inch lbs	126 - 131	.50	1
28506	10 - 50		2 Inch lbs	133 - 138	.59	1
28508	20 - 70		2 Inch lbs	137 - 142	.74	1

Above includes Micro Bit Holder 28583

See 4mm Micro Bits on Page 7

\* +/- 10% (This unit only)



#### 285 Adjustable TorqueVario-S Handle - In Newton Meter Scale

EN ISO 6798, BS EN 26789, ASME B107.14M. Ergonomic molded multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when the torque setting has been attained, automatically resets for next torque cycle.

Item No.	Newton				
	Meter Scale	Increments	mm	lbs.	pkg.
28550*	0.1 - 0.6Nm	.02 Nm	122 - 127	.35	1
28551	0.4 - 1.0Nm	.05 Nm	122 - 127	.35	1
28552	0.8 - 2.0Nm	.10 Nm	126 - 131	.45	1
28553	1.0 - 5.0Nm	.20 Nm	133 - 138	.55	1
28554	2.0 - 8.0Nm	.25 Nm	137 - 142	.70	1

\* +/- 10% (This unit only)



All TorqueVario models include Torque setting adjustment tool