WILTON® TRADESMAN

A: Steel Pipe Jaws:

Fixed Jaws Hold Up to 3-1/2" Pipe

B: Max Jaw Capacity:

MADE IN THE

STRAIGH

UNBREAKABLI Spindifænili

Up to 7" Jaw Opening For Jobs Demanding Maximum Holding Capacity

C: Reversible Jaw Inserts:

Standard serrated jaws for extra grip or smooth to prevent marring on softer surfaces

Stock Number	Model	Jaw Width (In.)	Jaw Opening (In.)	Throat Depth (In.)	Pipe Jaw Capacity (In.)	Ship Wt. (Lbs.)				
WILTON® TRADESMAN - SWIVEL BASE										
63199	1745	4-1/2	4	3-1/4	1/4 - 2-1/2	2 42				
63200	1755	5-1/2	5	3-3/4	1/4 – 3	53				
63201	1765	6-1/2	6-1/2	4	1/4 - 3-1/2	2 73				
63202	1780A	8	7	4-3/4	1/8 - 3-1/2	2 109				

TARGET USERS

С

- Tradesman
- Maintenance Shops
- Construction Sites

В



WILTON[®] MECHANIC

A: 30,000 PSI Ductile Iron Body:

С

Heavy-Duty Castings Are Built For Rugged Use and Extended Life

- B: Lifetime Lubrication: Grease is Permanently Sealed In For Trouble-Free Service
- C: Hi-Visibility Yellow: Conforms to OSHA standards for Physical Hazards Regulation #1910.144

TARGET USERS

- Professional Mechanics
- Automotive Maintenance
- Maintenance and Repair

Stock Number	Model	Jaw Width (In.)	Jaw Opening (In.)	Throat Depth (In.)	Pipe Jaw Capacity (In.)	Ship Wt. (Lbs.)				
WILTON® 740 SERIES MECHANICS VISES - SWIVEL BASE										
21300	744	4	4-1/2	3-7/16	1/4 – 2	37				
21400	745	5	5-1/4	3-3/4	1/4 – 2-1/2	50				
21500	746	6	5-3/4	4-1/8	1/4 – 3-1/2	64				
21800	748A	8	8-1/4	4-3/4	1/4 – 3-1/2	89				
WILTON® HIGH-VISIBILITY SAFETY VISES - SWIVEL BASE										
63187	1550	5	5-1/4	3-3/4	1/4 - 2-1/2	50				
63188	1560	6	5-3/4	4-1/8	1/4 - 3-1/2	64				



HARDENED STEEL PIPE JAWS

Replaceable and Reversible, Designed to Hold Pipe From 1/4" Up to A Maximum of 3-1/2"



SEALED CONSTRUCTION Enclosed Design Protects All Moving Parts Locking Out Dust, Chips, and Moisture



4 MOUNTING POSTS Provides Secure Hold To Your Bench Top, Truck, Or Work Station.

