VH324AWKGL

Heavy Duty Safety Switch Fused Viewing Window Type 12 240V 200A 3 POLE ground



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Field installed kit available
Number of Poles	3
Current Rating	200 A
Voltage Rating	250 V DC 240 V AC
Enclosure Rating	NEMA 12 galvannealed steel
Motor power hp	15 Hp at 240 V AC 50-60 Hz for 1 phase motors 25 Hp at 240 V AC 50-60 Hz for 3 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors 40 hp at 250 V DC

Complementary

Short-circuit current	10 KA for H, K, J or R without fuse rejection clips 200 KA for R with fuse rejection clips 200 kA for J
Fuse type	H or K R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 6250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in ² (13.3127 mm ²) (AWG 6250 kcmil)
Depth	9.02 in (229.11 mm)
Width	17.01 in (432.05 mm)
Height	28.93 in (734.82 mm)
Net Weight	55.01 lb(US) (24.95 kg)
Services	Factory installation
Condition of use	For USA For Mexico

Environment

	1 U U U 1 CU E007E	
	UL listed file E2875	
Certifications	UL listed file E28/5	

Ordering and shipping details

Category	00113-H&HU SW,2&3P,N12,30-200A
Discount Schedule	DE1
GTIN	3606485893747
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.25 in (48.895 cm)
Package 1 Width	9.00 in (22.86 cm)
Package 1 Length	31.88 in (80.9625 cm)
Package 1 Weight	55.12 lb(US) (25 kg)