

Customer Specification PART NO. FIT-221B-1/16

Construction

| 1) Tubing Type | Heat Shrinkable Tubing | |
|---|-------------------------|--|
| 2) Tubing Material | Cross Linked Polyolefin | |
| 3) Minimum Supplied ID(In) | 0.063 | |
| 4) Maximum Recovered ID (In) | 0.031 | |
| 5) Nominal Recovered Wall Thickness(In) | 0.017 | |
| 6) Color(s) | BLACK, BLUE, CLEAR | |

Applicable Specifications

| 1) UL | Standard 224 (Except Clear) | |
|----------------------|--|--|
| 2) CSA International | Standard 198 (Except Clear) | |
| 3) Other | AMS-DTL-23053/5 Class 1 (Except Clear) | |
| | AMS-DTL-23053/5 Class 2 (Clear Only) | |

Environmental

| 1) EU Directive 2011/65/EU(RoHS2): | | |
|-------------------------------------|---|--|
| | All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C. | |
| 2) REACH Regulation (EC 1907/2006): | | |
| | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration. | |
| 3) California Proposition 65: | The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65. | |

Properties