


Stem kits¹

ELA US12 Signature® LE standard or emergency, Precise® LRP with TM option, Quantum®, Titan® LED




NOTES:

- 1 Stem color is brushed aluminum. Standard canopy color is brushed aluminum. To order white or black canopy, add **W** or **B** to catalog number. For other lengths, replace 12 with appropriate stem length in inches. Example: ELA US24.
- 2 See page 450 for additional wireguard information.
- 3 Supplemental emergency circuits designed for normally off operation only.


Wireguards²

ELA WGEX Back-mount wireguard (shown) 13 5/8"W x 13 5/8"H x 4 3/4"D
ELA WGEXT Top-mount wireguard 14"W x 11"H x 6 3/4"D
ELA WGEXE End-mount wireguard 15"W x 11"H x 4 3/4"D
ELA WGHQM Back mount for LHQM combo 28" W x 15" H x 8" D



DC input kits³

LED Signature® Series
ELA LEDC6 6V 12W kit
ELA LEDC12 12V 12W kit



Exit Options and Compatibility

Family	Options													
	EL	N	SD	X2	F	FA	FI	HO	DL	TP	VR	LDC12/48	CSA	4X
LE				■ ¹										
LE EL N		□												
LRE				■ ¹										
LRE EL N		□	□											
LQM				■										
LQM EL N		□												
LHQM	□	■						■						
LRP				■ ¹										
LRP EL N		□												
LX										■				
LX EL N		□								■				
LV				■ ¹						□	□			
LV EL N		□								□	□			

□ Standard
 ■ Option available
 (blank) Option not available

Options

- EL** Lead-calcium battery
- N** Nickel-cadmium battery³
- SD** Self-diagnostics^{3,4}
- X2** Lamps wired on two separate circuits^{5,6}
- F** Flashing emergency operation^{3,4,6}
- FA** Flashing and audible emergency operation^{3,4,6}
- FI** Fire alarm flashing interface^{4,5,6}
- HO** High-output battery⁵
- DL** UL Listed for damp locations
- TP** Tamperproof Torx-head screws
- VR** Vandal-resistant shield (polycarbonate, .1" thick)
- LDC12/48** 12-48V DC input for LED lamps²
- CSA** CSA Certified
- 4X** NEMA 4X suitable for wet-mounting applications

NOTES:

- 1 Must specify input voltage.
- 2 Supplemental emergency circuits designed for *normally off* operation only. CSA Certified product only.
- 3 Only available with exits containing battery.
- 4 Not available with X2 option.
- 5 Not available with flashing option.
- 6 Not available with CSA Certified product.

Exit Replacement Batteries

Family	Batteries								
	ELB 06042 lead-calcium L: 2-3/4 (70) W: 1-7/8 (48) H: 4-1/8 (102)	ELB 0607 lead-calcium L: 4 (102) W: 1-1/2 (38) H: 6 (152)	ELB 0610 lead-calcium L: 6 (152) W: 2 (51) D: 4 (102)	ELB 1P201N nickel-cadmium L: 1-5/8 (43) Dia: 3/4 (19)	ELB 4814N nickel-cadmium L: 3-1/2 (89) W: 1 (25) H: 1-3/4 (44)	ELB 0604N nickel-cadmium L: 3-7/8 (98) W: 2-3/8 (60) H: 2-3/8 (60)	ELB 0701N nickel-cadmium L: 5-1/4 (133) W: 1 (25) H: 1-3/4 (44)	ELB 1201N nickel-cadmium L: 1-5/8 (43) Dia: 3/4 (19)	ELB 1P201N2 nickel-cadmium L: 1-5/8 (43) Dia: 3/4 (19)
QM EL/X EL	■								■ ⁹
LHQM ¹ /LQM EL ²	■								
LHQM ² /HQM		■	■ ⁷						
LX EL N				■					
LQM EL N ⁴ /LE EL N ⁵							■		
LV EL N					■ ⁸		■ ¹⁰		
LQM ELN ⁶								■	

■ Battery available
 (blank) Battery not available

Not all batteries and equipment are shown. Consult factory for additional requirements. All dimensions are inches (millimeters) unless otherwise noted.

NOTES:

- 1 Series 15-16.
- 2 Series 10-12.
- 3 Series 10-14.
- 4 Series 20-23.
- 5 Series 20-21.
- 6 Series 30.
- 7 With HO option.
- 8 Single face, no options.
- 9 With N option.
- 10 Double face, no options.