

Pneumatic Quick-Disconnect Lockout

- Isolates pneumatic energy without the expense and inconvenience of installing in-line lockout valves
- Device is applied to the male fitting, isolating equipment from all compressed air sources
- Accommodates the majority of 1/4", 1/8", 1/2" male fittings
- Hole in center of device allows for permanent storage on an air hose and a loop on the side can be used to hang the hose and lockout device
- Accommodates padlock with up to 1/4" shackle

| Catalog # | Description | Qty. |
|-----------|-------------------|------|
| 64221 | Pneumatic Lockout | 1 |
| 65645 | Pneumatic Lockout | 6 |



Prinzing Gas Cylinder Lockout

- Prevents access to the main cylinder valve
- No need to match your lockout device to varying diameters and threads of cylinder caps
- Accommodates neck rings up to 3-1/2" diameter
- Easy and efficient installation saves you time

| Catalog # | Description |
|-----------|----------------------|
| LM023E | Gas Cylinder Lockout |



SMC Air Line Regulator Lockout

- Enables regulator to be locked in the on, off or throttled position
- Easy installation: remove snap cap, install lockout on regulator rod, snap replacement cap on regulator
- Comes with lockout, cap and allen wrench. Padlock not included

| Catalog # | Description |
|-----------|---|
| 64539 | Lockout for Miniature SMC Models AR2000 / NAR2000 |
| 64540 | Lockout for Intermediate SMC Models AR3000 / NAR3000 |



Prinzing Cylinder Tank Lockout

- Used to lockout cylinder tanks, including propane tanks on fork trucks and stand alone propane tanks
- Apply with ease to prevent access to the valve handle
- Designed to fit in tight spaces
- Valve stem hole is 1.25" in diameter
- Made of rugged polystyrene plastic

| Catalog # | Description |
|-----------|-----------------------|
| SD02M | Cylinder Tank Lockout |



Snap Cap™ Gas Cylinder Lockout

- Designed to fit most North American high and low pressure gas cylinders
- Meets DOT standards
- Denies access to the main cylinder control and regulator attachment
- Powder coated welded steel construction is extremely durable

| Catalog # | Description | Color |
|-----------|---|--------|
| 90496 | 6.5" x 3-1/8" x 11 UN, High Pressure Fine Thread | Yellow |
| 95137 | 6.5" x 3-1/2" x 11 UN, Low Pressure Fine Thread | Yellow |
| 95138 | 6.5" x 3-1/8" x 11 UN, High Pressure Coarse Thread | Yellow |
| 95139 | 6.5" x 3-1/2" x 11 UN, Low Pressure Coarse Thread | Yellow |



Want to learn more about Lockout Tagout?

- Download the 5 Steps to an Effective Lockout Tagout Program Whitepaper
- View Brady's full line of Lockout Tagout product solutions

BradyID.com/lockouttagout

