



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



## Main

|                                    |  |
|------------------------------------|--|
| Range of product                   | Altivar Process ATV600   |
| Product or component type          | Variable speed drive   |
| Product specific application       | Process and utilities  |
| Device short name                  | ATV650   |
| Variant                            | Standard version   |
| Product destination                | Synchronous motors<br>Asynchronous motors  |
| Mounting mode                      | Wall mount   |
| EMC filter                         | Integrated 492.13 ft (150 m) EN/IEC 61800-3 category C3  |
| IP degree of protection            | IP55IEC 61800-5-1<br>IP55IEC 60529   |
| Degree of protection               | UL type 12 UL 508C   |
| Type of cooling                    | Forced convection  |
| Supply frequency                   | 50...60 Hz - 5...5 %   |
| Phase                              | 3 phase  |
| [Us] rated supply voltage          | 380...480 V - 15...10 %  |
| Motor power kW                     | 90 kW normal duty)<br>75 kW heavy duty)  |
| Maximum Horse Power Rating         | 125 Hp normal duty<br>100 hp heavy duty)   |
| Line current                       | 156.2 A 380 V normal duty)<br>135.8 A 480 V normal duty)<br>134.3 A 380 V heavy duty)<br>118.1 A 480 V heavy duty) |
| Prospective line I <sub>sc</sub>   | 50 kA  |
| Apparent power                     | 112.9 KVA 480 V normal duty)<br>98.2 kVA 480 V heavy duty)   |
| Continuous output current          | 173 A 2.5 kHz normal duty<br>145 A 2.5 kHz heavy duty  |
| Maximum transient current          | 190.3 A 60 s normal duty)<br>217.5 A 60 s heavy duty)  |
| Asynchronous motor control profile | Variable torque standard<br>Optimized torque mode<br>Constant torque standard                                      |
| Synchronous motor control profile  | Permanent magnet motor<br>Synchronous reluctance motor   |
| Output frequency                   | 0.0001...0.5 kHz   |
| Speed drive output frequency       | 0.1...599 Hz   |
| Nominal switching frequency        | 2.5 kHz  |
| Switching frequency                | 2.5...8 kHz with derating factor<br>2...8 kHz adjustable   |
| Safety function                    | STO (safe torque off) SIL 3  |
| Discrete input logic               | 16 preset speeds   |

|                             |   |
|-----------------------------|---|
| Communication port protocol | Modbus TCP<br>Modbus serial<br>Ethernet   |
| Option card                 | Slot A communication module, Profibus DP V1<br>Slot A communication module, Profinet<br>Slot A communication module, DeviceNet<br>Slot A communication module, Modbus TCP/EtherNet/IP<br>Slot A communication module, CANopen daisy chain RJ45<br>Slot A communication module, CANopen SUB-D 9<br>Slot A communication module, CANopen screw terminals<br>Slot A/slot B digital and analog I/O extension module<br>Slot A/slot B output relay extension module<br>Slot A communication module, Ethernet IP/Modbus TCP/MD-Link<br>Communication module, BACnet MS/TP<br>Communication module, Ethernet Powerlink |

## Complementary

|                                     |  |
|-------------------------------------|--|
| Output voltage                      | $\leq$ power supply voltage  |
| Permissible temporary current boost | 1.1 x $I_n$ 60 s normal duty)<br>1.5 x $I_n$ 60 s heavy duty)  |
| Motor slip compensation             | Adjustable<br>Not available in permanent magnet motor law<br>Automatic whatever the load<br>Can be suppressed  |
| Acceleration and deceleration ramps | Linear adjustable separately from 0.01...9999 s  |
| Braking to standstill               | By DC injection  |
| Protection type                     | Thermal protection motor<br>Safe torque off motor<br>Motor phase break motor<br>Thermal protection drive<br>Safe torque off drive<br>Overheating drive<br>Overcurrent between output phases and earth drive<br>Overload of output voltage drive<br>Short-circuit protection drive<br>Motor phase break drive<br>Overvoltages on the DC bus drive<br>Line supply overvoltage drive<br>Line supply undervoltage drive<br>Line supply phase loss drive<br>Overspeed drive<br>Break on the control circuit drive |
| Frequency resolution                | Display unit 0.1 Hz<br>Analog input 0.012/50 Hz  |
| Electrical connection               | Control removable screw terminals 0.5...1.5 mm <sup>2</sup> AWG 20...AWG 16<br>Motor screw terminal 120 mm <sup>2</sup> AWG 4...250 kcmil<br>Line side screw terminal 95 mm <sup>2</sup> AWG 3/0...250 kcmil   |
| Connector type                      | RJ45 on the remote graphic terminal)Ethernet/Modbus TCP<br>RJ45 on the remote graphic terminal)Modbus serial   |
| Physical interface                  | 2-wire RS 485 Modbus serial  |
| Transmission frame                  | RTU Modbus serial  |
| Transmission rate                   | 10/100 Mbit/s Ethernet IP/Modbus TCP<br>4.8, 9.6, 19.2, 38.4 kbit/s Modbus serial  |
| Exchange mode                       | Half duplex, full duplex, autonegotiation Ethernet/Modbus TCP  |
| Data format                         | 8 bits, configurable odd, even or no parity Modbus serial  |
| Type of polarization                | No impedance Modbus serial   |
| Number of addresses                 | 1...247 Modbus serial  |
| Method of access                    | Slave Modbus TCP   |
| Supply                              | External supply for digital inputs 24 V DC 19...30 V), <1.25 mA overload and short-circuit protection<br>Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection<br>Internal supply for digital inputs and STO 24 V DC 21...27 V), <200 mA overload and short-circuit protection  |

|                           |  |
|---------------------------|--|
| Local signalling          | Local diagnostic 3 LEDs<br>Embedded communication status 3 LEDs dual colour)<br>Communication module status 4 LEDs dual colour)<br>Presence of voltage 1 LED red)  |
| Width                     | 13.58 in (345 mm)  |
| Height                    | 49.21 in (1250 mm)   |
| Depth                     | 14.76 in (375 mm)  |
| Analogue input number     | 3  |
| Analogue input type       | AI1, AI2, AI3 software-configurable voltage 0...10 V DC 30 kOhm 12 bits<br>AI1, AI2, AI3 software-configurable current 0...20 mA/4...20 mA 250 Ohm 12 bits   |
| Discrete input number     | 8  |
| Discrete input type       | DI1...DI6 programmable, 24 V DC <= 30 V)3.5 kOhm<br>DI5, DI6 programmable as pulse input 0...30 kHz, 24 V DC <= 30 V)<br>STOA, STOB safe torque off, 24 V DC <= 30 V)> 2.2 kOhm  |
| Input compatibility       | DI1...DI6 discrete input level 1 PLC EN/IEC 61131-2<br>DI5, DI6 discrete input level 1 PLC IEC 65A-68<br>STOA, STOB discrete input level 1 PLC EN/IEC 61131-2  |
| Discrete input logic      | Positive logic (source) DI1...DI6), < 5 V, > 11 V<br>Negative logic (sink) DI1...DI6), > 16 V, < 10 V<br>Positive logic (source) DI5, DI6), < 0.6 V, > 2.5 V<br>Positive logic (source) STOA, STOB), < 5 V, > 11 V   |
| Analogue output number    | 2  |
| Analogue output type      | Software-configurable voltage AO1, AO2 0...10 V DC 470 Ohm 10 bits<br>Software-configurable current AO1, AO2 0...20 mA 10 bits   |
| Sampling duration         | 2 Ms +/- 0.5 ms DI1...DI4) - discrete input<br>5 Ms +/- 1 ms DI5, DI6) - discrete input<br>5 Ms +/- 0.1 ms AI1, AI2, AI3) - analog input<br>10 ms +/- 1 ms AO1) - analog output  |
| Accuracy                  | +/- 0.6 % AI1, AI2, AI3 for a temperature variation 60 °C analog input<br>+/- 1 % AO1, AO2 for a temperature variation 60 °C analog output   |
| Linearity error           | AI1, AI2, AI3 +/- 0.15 % of maximum value analog input<br>AO1, AO2 +/- 0.2 % analog output   |
| Relay output number       | 3  |
| Relay output type         | Configurable relay logic R1 fault relay NO/NC 100000 cycles<br>Configurable relay logic R2 sequence relay NO 100000 cycles<br>Configurable relay logic R3 sequence relay NO 100000 cycles  |
| Refresh time              | Relay output R1, R2, R3)5 ms +/- 0.5 ms)   |
| Minimum switching current | Relay output R1, R2, R3 5 mA 24 V DC   |
| Maximum switching current | Relay output R1, R2, R3 resistive, cos phi = 1 3 A 250 V AC<br>Relay output R1, R2, R3 resistive, cos phi = 1 3 A 30 V DC<br>Relay output R1, R2, R3 inductive, cos phi = 0.4 7 ms 2 A 250 V AC<br>Relay output R1, R2, R3 inductive, cos phi = 0.4 7 ms 2 A 30 V DC |
| Isolation                 | Between power and control terminals  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Insulation resistance                 | > 1 MOhm 500 V DC for 1 minute to earth  |
| Noise level                           | 69.9 dB 86/188/EEC   |
| Operating position                    | Vertical +/- 10 degree   |
| Maximum THDI                          | <48 % from 80...100 % of load IEC 61000-3-12   |
| Electromagnetic compatibility         | Electrostatic discharge immunity test level 3 IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 IEC 61000-4-3<br>Electrical fast transient/burst immunity test level 4 IEC 61000-4-4<br>1.2/50 µs - 8/20 µs surge immunity test level 3 IEC 61000-4-5<br>Conducted radio-frequency immunity test level 3 IEC 61000-4-6 |
| Pollution degree                      | 2 EN/IEC 61800-5-1   |
| Vibration resistance                  | 1.5 mm peak to peak 2...13 Hz)IEC 60068-2-6<br>1 gn 13...200 Hz)IEC 60068-2-6  |
| Shock resistance                      | 15 gn 11 ms IEC 60068-2-27   |
| Relative humidity                     | 5...95 % without condensation IEC 60068-2-3  |
| Ambient air temperature for operation | 5...104 °F (-15...40 °C) without)<br>104...122 °F (40...50 °C) with derating factor)   |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)   |
| Operating altitude                    | <= 3280.84 ft (1000 m) without<br>1000...4800 m with current derating 1 % per 100 m  |

|                              |  |
|------------------------------|--|
| Environmental characteristic | Chemical pollution resistance class 3C3 EN/IEC 60721-3-3<br>Dust pollution resistance class 3S3 EN/IEC 60721-3-3   |
| Standards                    | UL 508C<br>EN/IEC 61800-3<br>Environment 1 category C2 EN/IEC 61800-3<br>Environment 2 category C3 EN/IEC 61800-3<br>EN/IEC 61800-5-1<br>IEC 61000-3-12<br>IEC 60721-3<br>IEC 61508<br>IEC 13849-1 |
| Product certifications       | UL<br>DNV-GL<br>Bureau Veritas<br>TÜV<br>ABS<br>CSA<br>ATEX INERIS<br>REACH  |
| Marking                      | CE   |

### Ordering and shipping details

|                     |                             |
|---------------------|-----------------------------|
| Category            | 22207 - ATV630 FRAMES 5 & 6 |
| Discount Schedule   | CP4E                        |
| GTIN                | 00785901791409              |
| Package weight(Lbs) | 0.90 kg (1.98 lb(US))       |
| Returnability       | No                          |
| Country of origin   | CN                          |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |