

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product or component type	Contactors
Type	8502S
Control Circuit Type	Control circuit transformer
Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Contactors Type	Non-reversing
Current Rating	540 A
Number of Poles	3P
Phase	3 phase
Horsepower Rating	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Pilot Light	No indicator
Auxiliary Contacts	Without
Control Circuit Fusing	2 fuses (primary)
Electrical connection	Screw clamp terminals
Enclosure Type	Not rated (open device)
Product certifications	CSA UL listed
NEMA size	6
Height	28.07 in (713 mm)
Depth	9.02 in (229 mm)
Width	12.32 in (313 mm)

Ordering and shipping details

Category	21195 - 8502,36 SH,SJ(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901882688
Package weight(Lbs)	35.11 kg (77.4 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------