

EZ FLEX[®] Electrical Nonmetallic Tubing

Meets specifications: NEMA TC-13 and NEC Article 331.

Suitable for use with 90°C conductors.

CANTEX EZ-FLEX ENT is a high performance lower cost alternative to electrical metallic tubing. Non-conductive and corrosion resistant.

EZ-FLEX not only costs less than metal tubing but installation time is dramatically reduced, saving expensive labor cost.

Corrugated design allows bending by hand, eliminating the necessity of bending equipment and special tools. Reduced inner surface area cuts down on drag so that wire pulling is accomplished easier and faster.

U.L. Listed EZ-FLEX is used in circuits of 600 volts or less. Minimum installation temperature is -4°F (-20°C) and maximum ambient temperature is 122°F (50°C). EZ-FLEX is made in electric blue color for easy identification.



Straight Length-10'

PART NO.	SIZE	PIECES PER PACK	FEET PER PACK	UPC-ITF 3 00 PKG88700	PACK WT.
A51AE11	1/2	360	3600	51001 3	432
A51AG11	3/4	400	4000	51021 1	560
A51BA11	1	240	2400	12008 3	408



Coils

PART NO.	SIZE	FEET PER COIL	FEET PER PKG	UPC-ITF 3 00 PKG88700	PKG WT.
A51AEB1	1/2	200	400	02024 6	48
A51AGA1	3/4	200	200	02026 0	28
A51BAA1	1	100	100	01616 4	17



Reels

PART NO.	SIZE	FEET PER REEL	UPC-ITF 3 00 PKG88700	PKG WT. (Weight of reel not included)
A51AEQ1	1/2	1500	51019 8	180
A51AEK1	1/2	5000	04226 2	600
A51AGJ1	3/4	1000	51038 9	140
A51BAJ1	1	1000	01625 6	170

Note: U.L. Listed longer lengths are available on request. 1/2" – 5000' and 3/4" – 3000'



REELS OF RED AND YELLOW EZ FLEX ARE AVAILABLE