

Schedule 40 Conduit - Bell End

CANTEX

Meets specifications UL 651 and NEMA TC 2
 Rated for 90° C Cable
 Sunlight Resistant
 10' Lengths



Schedule 40 Conduit Belled End 10' Lengths



Part No.	Size	O.D.	I.D.	Min. Wall	Bell Depth	Approx. Wt/Ft	Feet per Pack
A52AE12	1/2	.840	.622	.109	1.750	.162	6,000
A52AE12H	1/2	.840	.622	.109	1.750	.162	3,000
A52AG12	3/4	1.050	.824	.113	2.000	.216	4,400
A52AG12H	3/4	1.050	.824	.113	2.000	.216	2,200
A52BA12	1	1.315	1.049	.133	2.250	.320	3,600
A52BA12H	1	1.315	1.049	.133	2.250	.320	1,800
A52BC12	1-1/4	1.660	1.380	.140	2.500	.434	3,300
A52BC12H	1-1/4	1.660	1.380	.140	2.500	.434	1,650
A52BE12	1-1/2	1.900	1.610	.145	2.750	.520	2,250
A52BE12H	1-1/2	1.900	1.610	.145	2.750	.520	1,130
A52CA12	2	2.375	2.067	.154	3.250	.699	1,400
A52CE12	2-1/2	2.875	2.469	.203	3.500	1.108	930
A52DA12	3	3.500	3.068	.216	4.000	1.450	880
A52DE12	3-1/2	4.000	3.548	.226	4.250	1.744	630
A52EA12	4	4.500	4.026	.237	4.750	2.067	570
A52FA12	5	5.563	5.047	.258	5.750	2.801	380
A52GA12	6	6.625	6.065	.280	6.325	3.636	260
A52JA12	* 8	8.652	7.981	.322	6.500	5.474	180

* Non UL

Note: 20' length available on request

Schedule 40 conduit complies with federal and military specifications by conforming to UL 651.