

## CONDUIT BODIES • COVERS • GASKETS

### Threaded LR Conduit Body Form 7 Gray Iron



#### Applications

To provide access to conductors for pulling, splicing and maintenance

#### Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete

#### Standard Materials

Cover and clips - Gray iron steel  
Screws - Stainless steel  
Gasket - Neoprene

#### Standard Finish


Zinc plated with aluminum enamel paint

#### Applicable Third Party Standards


- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- CSA 243470
- UL Listed File # E208392



LRKON



LR-CGKON



#### Threaded LR Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
LR17KON	1/2"	4.563	2.125	1.438	5	89.6
LR27KON	3/4"	5.125	2.375	1.688	5	124.1
LR37KON	1"	6.063	2.688	1.875	5	149.5
LR47KON	1-1/4"	6.500	3.125	2.250	2	246.0
LR57KON	1-1/2"	7.188	3.500	2.500	2	324.0
LR67KON	2"	8.188	4.063	3.250	2	462.2

#### Threaded LR Conduit Bodies with Cover and Gasket

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
LR17-CGKON	1/2"	4.563	2.125	1.688	5	104.3
LT27-CGKON	3/4"	5.125	2.375	1.938	5	142.5
LR37-CGKON	1"	6.063	2.688	2.063	5	175.2
LR47-CGKON	1-1/4"	6.500	3.125	2.563	2	278.8
LR57-CGKON	1-1/2"	7.188	3.500	2.813	2	362.6
LR67-CGKON	2"	8.188	4.063	3.563	2	515.2

Aluminum available upon request