

CONDUIT BODIES • COVERS • GASKETS

Aluminum Die Cast Threaded LB Conduit Bodies for Rigid • IMC conduit



Applications

To provide access to conductors for pulling, splicing and maintenance

Features

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet location

Standard Materials


- Die cast aluminum
- Copper free
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards


- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



ALBKON



ALB-CGKON



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
Aluminum Die Cast Threaded LB Conduit Bodies							
ALB1KON	1/2"	4.313	1.313	2.188	10	100	24.3
ALB2KON	3/4"	5.063	1.563	2.438	10	50	37.2
ALB3KON	1"	5.875	1.750	2.750	5	25	46.3
ALB4KON	1-1/4"	7.813	2.500	3.438	2	10	97.7
ALB5KON	1-1/2"	7.813	2.500	3.438	2	10	90.9
ALB6KON	2"	10.063	3.125	4.313	1	5	221.6
ALB7KON	2-1/2"	12.813	4.500	5.313	-	1	365.7
ALB8KON	3"	12.813	4.500	5.813	-	1	429.7
ALB9KON	3-1/2"	15.625	5.563	7.063	-	1	936.9
ALB10KON	4"	15.625	5.563	7.063	-	1	851.4
Aluminum Die Cast Threaded LB Conduit Bodies with Stamped Aluminum Cover & Neoprene Gasket							
ALB1CGKON	1/2"	4.313	1.313	2.438	10	100	30.5
ALB2CGKON	3/4"	5.063	1.563	2.688	10	50	44.6
ALB3CGKON	1"	5.875	1.750	3.000	5	25	56.3
ALB4CGKON	1-1/4"	7.813	2.500	3.688	2	10	116.8
ALB5CGKON	1-1/2"	7.813	2.500	3.688	2	10	110.0
ALB6CGKON	2"	10.063	3.125	4.563	1	5	253.9
ALB7CGKON	2-1/2"	12.813	4.500	5.563	-	1	427.4
ALB8CGKON	3"	12.813	4.500	6.188	-	1	491.4
ALB9CGKON	3-1/2"	15.625	5.563	7.313	-	1	1060.1
ALB10CGKON	4"	15.625	5.563	7.313	-	1	974.6