

CONDUIT BODIES • COVERS • GASKETS

Aluminum Die Cast Threaded LL Conduit Bodies for Rigid • IMC conduit



Applications

To provide access to conductors for pulling, splicing and maintenance

Features


- Tapered threaded hubs - NPT
- Suitable for use in concrete
- Wet Location

Standard Materials


- Die cast aluminum
- Copper free
- Covers - Stamped aluminum
- Gasket - Neoprene rubber

Applicable Third Party Standards

- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA: FB-1
- UL Listed File # E208392



ALLKON



ALLCGKON

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MASTER PACK	WEIGHT PER C
Aluminum Die Cast Threaded LL Conduit Body for Rigid						
ALL1KON	1/2"	4.313	2.063	1.375	100	24.5
ALL2KON	3/4"	5.063	2.250	1.625	50	36.8
ALL3KON	1"	5.875	2.625	1.875	25	45.2
ALL4KON	1-1/4"	7.813	3.625	2.5	10	97.9
ALL5KON	1-1/2"	7.813	3.625	2.5	10	91.9
ALL6KON	2"	10.603	4.438	3.375	5	245.0
ALL7KON	2-1/2"	12.813	5.750	4	1	387.6
ALL8KON	3"	12.813	5.750	4.5	1	439.2
ALL9KON	3-1/2"	15.625	7.688	5.625	1	923.7
ALL10KON	4"	15.625	7.688	5.625	1	881.8
Aluminum Die Cast Threaded LL Conduit Body with Flat Cover & Gasket						
ALL1CGKON	1/2"	4.313	2.063	1.625	100	30.7
ALL2CGKON	3/4"	5.063	2.250	1.875	50	44.2
ALL3CGKON	1"	5.875	2.625	2.125	25	55.2
ALL4CGKON	1-1/4"	7.813	3.625	2.750	10	117.0
ALL5CGKON	1-1/2"	7.813	3.625	2.750	10	111.0
ALL6CGKON	2"	10.603	4.438	3.625	5	277.3
ALL7CGKON	2-1/2"	12.813	5.750	4.250	1	419.9
ALL8CGKON	3"	12.813	5.750	4.750	1	500.9
ALL9CGKON	3-1/2"	15.625	7.688	5.875	1	1046.9
ALL10CGKON	4"	15.625	7.688	5.875	1	1005.0